

***GOLDPARTNER***

**TRUCK & BUS RADIAL TYRES**



# CONTENTS

GP701	-----	01
GP701+	-----	02
GP701A	-----	03
GP702	-----	04
GP702A	-----	05
GP703	-----	06
GP704	-----	07
GP704A	-----	08
GP706	-----	09
GP706+	-----	10
GP708	-----	11
GP708+	-----	12
GP709A	-----	13
GP710	-----	14
GP710A	-----	15
GP711	-----	16
GP712	-----	17
GP712+	-----	18
GP712A	-----	19
GP715	-----	20
GP717	-----	21
GP717A	-----	22
GP718	-----	23
GP718A	-----	24
GP718A+	-----	25
GP719	-----	26
GP720	-----	27
GP720+	-----	28
GP720A	-----	29
GP721	-----	30
GP721+	-----	31
GP722	-----	32
GP722A	-----	33
GP729	-----	34
GP730	-----	35
GP730+	-----	36
GP731	-----	37
GP731+	-----	38
GP731A+	-----	39
GP731A++	-----	40
GP734	-----	41
GP735	-----	42
GP737	-----	43

# GP701



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Max Load(kg) Dual	Pressure(Kpa) Single	Pressure(Kpa) Dual	Inflated SW	Dimensions ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346

# GP701+



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	17.50	372

# GP701A



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	930	930	300	1088	17.5	343
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.5	351

  
**GP702**



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

**Benefits**



Long Haul



Longer Mileage



Powerful Traction

**Vehicle**



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	11.50	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	16.50	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	16.50	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	16.50	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	16.50	360
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.50	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	16.50	318
295/60R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	15.50	335
315/60R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.50	351

# GP702A



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

## Benefits

## Vehicle



Long Haul



Longer Mileage



Powerful Traction



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	18.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	17.50	372
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	17.00	351

# GP703



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 zigzag longitudinal grooves provides excellent directional driving performance.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320



# GP704



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

## Benefits




Long Haul



Powerful Traction

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	13.00	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	18.50	346
12.00R20	18	K	154/151	8.50	3750	3450	830	830	315	1125	17.00	372
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	17.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	17.00	372
9.5R17.5	16	L	139/137	6.75	2430	2300	850	850	240	842	15.00	270
9.5R17.5	18	J	143/141	6.75	2725	2575	850	850	240	842	15.00	270
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	16.00	237
215/75R17.5	18	L	135/133	6.00	2180	2080	830	830	211	767	16.00	237
235/75R17.5	16	L	141/140	6.75	2575	2500	830	830	233	797	16.00	262
235/75R17.5	18	J	143/141	6.75	2725	2575	830	830	233	797	16.00	262
225/80R17.5	16	L	123/122	6.75	1550	1500	750	750	203	803	16.00	255
245/70R19.5	16	M	136/134	7.50	2240	2120	830	830	248	839	16.00	279
265/70R19.5	16	M	140/138	7.50	2500	2360	860	860	262	867	16.00	295
265/70R19.5	18	J	143/141	7.50	2725	2575	860	860	262	867	16.00	295
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	18.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	18.00	360
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	18.00	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	18.00	351

# GP704A



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

## Benefits




Long Haul



Powerful Traction

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	16.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	16.00	255
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	23.00	372
245/70R19.5	16	M	136/134	7.50	2240	2120	830	830	248	839	16.00	279
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	23.00	343

# GP706



- Driving wheel position for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.
- Strong block design increases braking power and traction performance.

## Benefits



Off Road



Powerful Traction



Mixed Surface

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1019	20.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	22.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	22.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	23.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	23.00	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	23.00	343
285/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	21.00	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	21.00	351
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	23.00	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	23.00	318

# GP706+



- Driving wheel position for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.
- Strong block design increases braking power and traction performance.

## Benefits



Off Road



Powerful Traction



Mixed Surface

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	J	152/149	8.0	3550	3250	930	930	293	1085	20.5	346
12.00R20	20	J	158/153	8.5	4000	3650	900	900	315	1125	21.5	372



- Suitable for driving position on paved road conditions. Suitable for middle and long haul usage on good road conditions.
- Special groove bottom design strengthens tire block and provides excellent self-cleaning ability.

**Benefits**



Long Haul



Longer Mileage



Comfort

**Vehicle**



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	M	144/142	8.25	2800	2650	720	720	279	1050	23.00	320
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	23.00	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	23.00	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	23.00	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1044	23.00	335
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1044	23.00	335
295/75R22.5	18	L	149/146	9.00	3250	3000	930	930	298	1044	23.00	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	23.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	23.00	318



# GP708+



- Suitable for driving position on paved road conditions. Suitable for middle and long haul usage on good road conditions.
- Special groove bottom design strengthens tire block and provides excellent self-cleaning ability.

## Benefits



Long Haul




Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	L	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1044	23.00	335
295/75R22.5	18	L	149/146	9.00	3250	3000	930	930	298	1044	23.00	335

# GP709A



- Suitable for middle/long distance trucks on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
425/65R22.5	20	K	165	13.00	5150		825	430	1124	15.00		

# GP710



- Deep and sturdy tread pattern for high mileage, stone & mud clearance. Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

## Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	22.00	343



# GP710A



- Deep and sturdy tread pattern for high mileage, stone & mud clearance. Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

## Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215 805	16.50	255
7.50R16LT	16	L	124/120	6.00G	1600 1400	770 770	215 805	16.50	255
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	16.00	278
9.00R20	16	K	144/142	7.00	2800 2650	900 900	259 1018	21.00	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	21.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	23.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	23.00	372
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	23.00	343
285/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	23.00	335

# GP711



- Suitable for driving wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
225/70R19.5	14	L	128/126	6.75	1800	1700	760	760	226	811	17.00	254
225/80R17.5	16	L	123/122	6.75	1550	1500	750	750	203	803	16.00	256
275/70R22.5	16	M	148/145	8.25	3150	2900	900	900	276	958	16.00	311
275/80R22.5	16	M	149/146	8.25	3250	3000	850	850	285	1026	16.00	320
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	21.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	21.00	318

# GP712



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

## Benefits




Long Haul



Powerful Traction

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	16.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	17.00	328
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	16.00	237
215/75R17.5	18	L	135/133	6.00	2180	2060	830	830	211	767	16.00	237
235/75R17.5	16	L	132/129	6.75	2000	1850	830	830	233	797	16.00	262
235/75R17.5	18	J	143/141	6.75	2725	2575	830	830	233	797	16.00	262
11R22.5	16	M	148/143	8.25	3000	2725	830	830	279	1050	17.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	17.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	17.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	19.50	360
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	17.00	335
315/70R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1014	17.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	17.00	351

# GP712+



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

## Benefits



Long Haul



Powerful Traction

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	21.00	320
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	21.00	335
315/70R22.5	18	M	154/150	9.00	3750	3350	800	800	312	1014	20.00	351
315/70R22.5	20	M	156/150	9.00	4000	3350	830	830	312	1014	20.00	351
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	23.00	351

# GP712A



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

## Benefits




Long Haul



Powerful Traction

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	930	930	300	1083	20.00	343
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	20.00	318

# GP715



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
8.5R17.5	12	L	121/120	6.00	1450	1400	620	620	215	802	13.00	242
9.5R17.5	16	L	139/137	6.75	2430	2300	850	850	240	842	13.00	270
9.5R17.5	18	J	143/141	6.75	2725	2575	850	850	240	842	15.00	270
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	14.00	237
215/75R17.5	18	L	135/133	6.00	2180	2060	830	830	211	767	14.00	237
235/75R17.5	16	L	132/129	6.75	2000	1850	830	830	233	797	14.00	262
235/75R17.5	18	J	143/141	6.75	2725	2575	830	830	233	797	14.00	262
265/70R19.5	16	M	140/138	7.50	2500	2360	860	860	262	867	14.00	295
265/70R19.5	18	J	143/141	7.50	2725	2575	860	860	262	867	14.00	295

# GP717



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

## Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
1000R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	19.00	328
1100R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	19.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	19.00	372
11R22.5	16	M	148/143	8.25	3000	2725	830	830	279	1050	19.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	19.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	19.00	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	23.00	360
285/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	23.00	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	23.00	351
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	23.00	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	23.00	318

# GP717A



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

## Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	930	930	300	1093	20.0	343





- Suitable for all wheel position of middle/long distance buses and trailer wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

**Benefits**



Long Haul



Longer Mileage



Comfort

**Vehicle**



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	14	M	144/142	8.25	2800	2650	720	720	279	1050	10.50	320
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	10.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	10.50	320
11R24.5	14	L	146/143	8.25	3000	2725	720	720	279	1104	10.50	318
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	10.50	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	10.50	318
295/75R22.5	14	L	144/141	9.00	2800	2575	760	760	298	1044	10.50	335
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1044	10.50	335
295/75R22.5	18	L	149/146	9.00	3250	3000	930	930	298	1044	10.50	335
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	10.50	318
285/75R24.5	16	L	147/144	8.25	3072	2800	830	830	283	1050	10.50	318



# GP718A



- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

## Benefits



Long Haul




Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	14.00	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.00	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	16.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
9R22.5	14	L	136/134	6.75	2240	2120	830	830	230	970	15.00	262
10R22.5	16	L	144/142	7.50	2800	2650	900	900	245	1020	16.00	290
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.50	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	16.50	318
225/70R19.5	14	L	128/126	6.75	1800	1700	760	760	226	811	13.00	254
225/80R17.5	16	L	123/122	6.75	1500	1500	825	825	203	803	13.00	254
245/70R19.5	16	M	136/134	7.50	2240	2120	830	830	248	839	14.00	279
285/70R19.5	16	M	146/144	8.25	3000	2800	900	900	283	901	14.00	318
255/70R22.5	16	L	140/137	7.50	2500	2300	830	830	255	930	15.00	287
275/70R22.5	16	M	148/145	8.25	3150	2900	900	900	276	958	16.00	311
275/80R22.5	16	M	149/146	8.25	3250	3000	850	850	285	1026	16.00	311
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	16.50	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	16.50	318
295/75R22.5	16	L	146/143	9.00	3000	2725	830	830	298	1044	16.50	335
295/75R22.5	18	L	149/146	9.00	3250	3000	930	930	298	1044	16.50	335
315/70R22.5	18	M	154/150	9.00	3750	3350	800	800	312	1014	16.50	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	19.00	351



# GP718A+



- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	18	M	149/146	8.25	3250	3000	830	830	279	1050	15.5	320
12R22.5	18	L	152/149	9.00	3550	3250	930	930	300	1084	15.5	343

# GP719



- Suitable for tipper trucks on tough road conditions such as mine and construction site.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom thereby resulting in a safer driving experience.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	18.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	18.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	18.50	346

# GP720



- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	148/143	8.25	3000	2725	830	830	279	1050	15.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	15.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	15.00	343
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	15.00	335
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.00	351

# GP720+



- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300		18.00	343
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298		18.00	335

# GP720A



- Suitable for all wheel positions of middle/long distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear grooves design provides excellent directional driving performance and prevents hydroplaning.

## Benefits



Long Haul




Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	16.50	343
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	18.00	335

# GP721



- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

## Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
295/60R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	23.00	335
295/60R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	23.00	335



# GP721+



- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

## Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	F	152/149	8.00	3550	3250	930	930	293	1085	23.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	24.00	372

# GP722



- Suitable for driving wheel position of vans on various road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience.

## Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1800	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	16.00	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	17.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
12.00R20	20	K	158/153	8.50	4000	3650	900	900	315	1125	19.00	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	20.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	20.00	343
315/80R22.5	18	F	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	21.00	351

# GP722A



- Suitable for driving wheel position of vans on various road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience.

## Benefits



Regional



Longer Mileage




Powerful Traction



Anti-chipping

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	21.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	21.00	346
12.00R20	20	K	158/153	8.50	4000	3650	900	900	315	1125	21.00	372

# GP729



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear groove design provide excellent directional driving performance and prevent hydroplaning .

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	15.50	360

# GP730



- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.

## Benefits



Long Haul




Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	16.00	372

# GP730+



- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12.00R24	20	K	180/157	8.50	4500	4125	900	900	315	1222	15.00	372

# GP731



- Suitable for middle/long distance on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

## Benefits



Long Haul



Longer Mileage



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	180	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	

# GP731+



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

## Benefits



Long Haul




Powerful Traction



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	



# GP731A+



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

## Benefits



Long Haul




Powerful Traction



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	

# GP731A++



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

## Benefits



Long Haul




Powerful Traction



Comfort

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	

# GP734



- Special design for anti-skidding and perfect handling.
- Central tread ensure excellent gripping and reduce rolling resistance.
- Unique technical formula improve the wear-resistance and stability..
- Suitable for middle/long distance on good road conditions.
- 4 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

### Benefits



Long Haul



Longer Mileage



Comfort

### Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
285/75R24.5	14	M	144/141	8.25	2800	2575	760	760	283	1050	10.50	318
285/75R24.5	16	M	147/144	8.25	3072	2800	830	830	283	1050	10.50	318

# GP735



- Safe and advance pattern design reduce rolling resistance and ensure tire fuel economy and high speed performance.
- Suitable for steering wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 5 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

## Benefits



## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
285/75R24.5	14	M	144/141	8.25	2800	2575	760	760	283	1050	16.50	318
285/75R24.5	16	M	147/144	8.25	3072	2800	830	830	283	1050	16.50	318

# GP737



- Suitable for drive positions.
- Mixed deep tread block, widened tread, increased grip performance.
- Design for on all types of non-paved roads.

## Benefits



Long Haul



Longer Mileage

## Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	23.00	342
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	23.00	360
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	23.00	351

## **HONGTYRE INTERNATIONAL FZE**

Add: NO.43 Bangkok Road, Qingdao Free Trade Zone, Qingdao, China.

Tel: +86-532- 86766013 +86-532- 86768126

+86-532- 86768852 +86-532- 86766033

+86-532- 86768057 +86-532- 86768067

+86-532- 86768860 +86-532- 86768065

Fax: +86-532-86769930

Email: [roadshine@hongtyre.com](mailto:roadshine@hongtyre.com);

Web: [www.hongtyre.com](http://www.hongtyre.com);