



ROADSHINE

PASSENGER CAR TYRE



CONTENTS

<i>RS901</i>	-----	1
<i>RS901+</i>	-----	2
<i>RS901A</i>	-----	3
<i>RS902</i>	-----	4
<i>RS902+</i>	-----	5
<i>RS902++</i>	-----	6
<i>RS902A</i>	-----	7
<i>RS903</i>	-----	8
<i>RS903+</i>	-----	9
<i>RS904</i>	-----	10
<i>RS904+</i>	-----	11
<i>RS904A</i>	-----	12
<i>RS905</i>	-----	13
<i>RS905+</i>	-----	14
<i>RS906</i>	-----	15-16
<i>RS906+</i>	-----	17
<i>RS906A</i>	-----	18
<i>RS907</i>	-----	19
<i>RS907+</i>	-----	20
<i>RS908</i>	-----	21
<i>RS909</i>	-----	22
<i>RS916</i>	-----	23
<i>RS920</i>	-----	24
<i>RS922</i>	-----	25-26
<i>RS922+</i>	-----	27
<i>RS922A</i>	-----	28
<i>RS922A+</i>	-----	29
<i>RS928</i>	-----	30
<i>RS930</i>	-----	31-32
<i>RS931</i>	-----	33
<i>RS932</i>	-----	34
<i>RS933</i>	-----	35

RS901



- 3 longitudinal grooves enhance water evacuation.
- Special more sipes and grooves design enhances the wet grip performance.
- Silent groove design decreases noise while tire rolling effectively.
- Enhanced shoulder design increases driving stability with high load.

Benefits



Comfort



Quiet



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
155R12C-8PR	88/86Q	4.5B	4.0B-5.0J	450	560	530	553	157	8.0
165R13C-8PR	94/93Q	4.5B	4.0J-5.0J	450	670	650	596	167	8.0
175R13C-8PR	97/95Q	5.0B	4.50B-5.50B	450	730	680	610	177	8.0
185R14C-8PR	102/100Q	5.5J	5.0J-6.0J	450	850	800	650	188	8.0
195R14C-8PR	106/104Q	5.5J	5.0J-6.0J	450	950	900	666	198	8.0
195R15C-8PR	106/104Q	5.5J	5.0J-6.0J	450	950	900	693	196	8.0
225/70R15C-8PR	106/103Q	6.5J	6.0J-7.0J	450	1120	1060	697	228	8.5
215R15C-8PR	110/109Q	6.0J	5.5J-6.5J	450	1060	1030	719	212	8.5

RS901+



- 3 longitudinal grooves enhance water evacuation.
- Special more sipes and grooves design enhances the wet grip performance.
- Silent groove design decreases noise while tire rolling effectively.
- Enhanced shoulder design increases driving stability with high load.

Benefits



Comfort



Mixed Surface



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
185R14C-8PR	102/100Q	5.5J	5.0J-6.0J	450	850	800	652	188	8.0
195R14C-8PR	106/104Q	5.5J	5.0J-6.0J	450	950	900	666	198	8.0
195R15C-8PR	106/104Q	5.5J	5.0J-6.0J	450	950	900	683	196	8.0

RS901A



- Three longitudinal "S" saw teeth groove design for excellent water drainage and good handling.
- Deep pattern + high saturation in contact with the ground + mixed pattern design + wear resistant compound, for much longer mileage.
- Mixed pattern design for shoulder, effectively reduce noise.

Benefits



Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
205R16C-8PR	110/108S	6.0J	5.5J-6.0J	450	1060	1000	734	208	9.0

RS902



- Multi-sipe design, improved grip on snow and icy roads, to guarantee its handling and braking performance.
- Block tread pattern design, high cross density, improved performance.
- 3D shoulder profile, improved traction and braking performance for rough application.
- Curved main groove design, increased tread rigidity, to avoid irregular wear under high load operation.
- Low sea-land ratio(Non-saturated) tread design, to guarantee load capability.

Benefits



Comfort



Powerful Traction



Excellent Handling



Off Road

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
195/70R15C-8PR	104/102S	6.0J	5.0J-6.0J	450	900	850	655	201	9.5
215/65R15C-8PR	104/102T	6.5J	6.0J-7.0J	450	900	850	661	221	9.5
215/70R15C-8PR	109/107S	6.5J	6.0J-7.0J	450	1030	975	683	221	9.5
185/75R16C-8PR	104/102S	5.0J	5.0J-6.0J	475	900	850	684	184	9.5
195/65R16C-8PR	104/102T	6.0J	5.5J-6.0J	475	900	850	660	201	9.5
195/75R16C-8PR	107/105S	5.5J	5.0J-6.0J	475	975	925	698	196	9.5
205R16C-8PR	110/108S	6.0J	5.5J-6.0J	450	1060	1000	734	208	9.0
215/65R16C-8PR	109/107T	6.5J	6.0J-7.0J	475	1030	975	686	221	9.5
215/75R16C-8PR	113/111S	6.0J	5.5J-7.0J	475	1150	1090	728	216	9.5
225/65R16C-8PR	112/110T	6.5J	6.0J-7.0J	475	1120	1060	698	228	10.0
235/65R16C-8PR	115/113T	7.0J	6.5J-7.5J	450	1215	1150	712	240	10.0

RS902+



- Three longitudinal "S" saw teeth groove design for excellent water drainage and good handling.
- Deep pattern + high saturation in contact with the ground + mixed pattern design + wear resistant compound, for much longer mileage.
- Mixed pattern design for shoulder, effectively reduce noise.

Benefits



Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
165R14C-8PR	97/95S	5.0J	5.0J-6.0J	450	710	690	620	165	9.5
175/75R14C-8PR	99/98S	5.0J	5.0J-6.0J	450	670	630	618	177	9.5
205R14C-8PR	109/107R	6.0J	5.5J-6.5J	450	1030	975	686	208	9.8
215/75R14C-8PR	112/110R	6.0J	5.5J-6.5J	475	1120	1060	678	216	9.5
185R15C-8PR	103/102R	5.5J	5.0J-6.0J	450	875	850	674	188	9.8
205/70R15C-8PR	108/104R	6.0J	5.5J-6.5J	450	950	900	669	209	9.5
185/75R16C-8PR	104/102R	5.0J	5.0J-6.0J	475	900	850	684	184	9.5
205/65R16C-8PR	107/105R	6.0J	5.5J-6.5J	475	975	925	672	209	9.5
215/70R16C-8PR	108/106R	6.0J	5.5J-7.0J	375	1000	950	708	221	9.5
225/75R16C-10PR	121/120R	6.0J	6.0J-7.0J	575	1450	1400	744	223	9.5

RS902++



- The extra-strong structure design ensures the impact resistance ability and offers tire high wear resistance.
- The main block pattern adopting with staggered arrangement and supplemented by the tiny pattern which outstanding improve the braking performance.

Benefits



Longer Mileage



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
5.00R12LT-10PR	88/88Q	3.50B	3.00B-4.00B	560	560	530	564	138	6.5

RS902A



- Multi-sipe design, improved grip on snow and icy roads, to guarantee its handling and braking performance.
- Block tread pattern design, high cross density, improved performance.
- 3D shoulder profile, improved traction and braking performance for rough application.
- Curved main groove design, increased tread rigidness, to avoid irregular wear under high load operation.
- Low sea-land ratio(Non-saturated) tread design, to guarantee load capability.

Benefits



Comfort



Powerful Traction



Excellent Handling



Off Road

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
185/75R16C-8PR	104/102R	5.0J	5.0J-6.0J	475	900	850	684	184	8.7

RS903



- Deep pattern + high saturation in contact with the ground + mixed pattern design + wear resistant compound, for much longer mileage.
- Special contour profile, 2% more contact area, improve the mileage and turning performance.
- Special pattern design, avoid stone or other thing clamped in the grooves.

Benefits



Wet Performance



Longer Mileage



Off Road

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
215/75R15	100S	6.0J	5.5J-7.0J	300	800		699	218	10.0
225/65R17	102H	6.5J	6.0J-8.0J	300	850		724	228	10.0
235/65R17	104T	7.0J	6.5J-8.5J	300	900		732	243	10.0
245/65R17	107T	7.0J	7.0J-8.5J	300	975		744	247	10.0
275/65R17	115T	8.0J	7.5J-9.5J	300	1215		784	276	10.0
30*9.50R15LT-6PR	104Q	7.5J	6.0J-8.0J	350	900		744	225	10.0
31*10.50R15LT-6PR	109Q	8.5J	7.0J-9.0J	350	1030		771	250	10.0
235/75R15LT-6PR	104/101Q	6.5J	6.0J-8.0J	350	900	825	727	232	10.0
245/75R16LT-10PR	120/116Q	7.0J	6.0J-8.0J	550	1400	1250	770	241	10.0

RS903+



- Deep pattern + high saturation in contact with the ground + mixed pattern design + wear resistant compound, for much longer mileage.
- Special contour profile, 2% more contact area, improve the mileage and turning performance.
- Special pattern design, avoid stone or other thing clamped in the grooves.

Benefits



Wet Performance



Longer Mileage



Off Road

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
P215/75R15	100S	6.5J	5.5J-7.0J	300	800		703	216	9.5
P255/70R15	108S	7.5J	6.0J-8.0J	300	1000		739	260	9.6
P215/70R16	100S	6.0J	5.5J-7.0J	300	800		708	221	9.6
235/70R16	106S	7.0J	6.0J-8.0J	300	950		736	240	9.6
P245/70R16	107S	7.0J	6.0J-8.0J	300	975		750	248	9.6
P255/70R16	111S	7.5J	6.5J-8.5J	300	1090		784	260	9.6
P265/70R16	112S	8.0J	7.5J-9.0J	300	1120		778	272	9.6
P265/75R16	116S	7.5J	7.0J-9.0J	300	1250		804	267	9.6
P275/70R16	114S	8.0J	7.0J-9.0J	350	1180		792	279	9.7
P265/65R17	112S	8.0J	7.5J-9.5J	300	1120		776	272	9.6
P265/70R17	115S	8.0J	7.0J-9.0J	300	1215		804	272	9.6
265/60R18	100S	8.0J	7.0J-9.0J	300	1060		775	272	9.6
P285/60R18	116S	8.5J	7.5J-9.0J	300	1250		799	292	9.6
265/60R20	111V	8.5J	7.5J-9.0J	340	1090		774	277	9.6
P275/60R20	115S	8.0J	7.5J-8.5J	300	1215		844	279	9.5
LT215/65R16-10PR	115/112Q	6.0J	5.5J-7.0J	550	1215	1120	772	216	11.0
LT225/75R16-10PR	115/112Q	6.0J	5.5J-7.0J	550	1215	1120	744	223	11.0
LT235/65R16-10PR	120/116Q	6.5J	6.0J-7.5J	550	1380	1260	806	235	12.5
LT245/75R16-10PR	120/116Q	7.0J	6.0J-8.0J	550	1380	1260	774	248	12.5
LT285/75R16-10PR	123/120Q	7.5J	7.0J-8.0J	550	1550	1400	804	267	12.5
LT285/75R16-8PR	122/119Q	8.0J	7.5J-8.5J	450	1500	1360	834	286	12.8
LT245/75R17-10PR	121/118Q	7.0J	6.5J-7.5J	550	1450	1320	800	248	12.5
LT285/70R17-10PR	121/118Q	8.0J	7.5J-8.5J	550	1450	1320	804	272	12.5
LT285/70R17-10PR	121/118Q	8.5J	7.5J-9.0J	550	1450	1320	832	292	12.5
LT275/65R18-10PR	123/120Q	8.0J	7.5J-8.5J	550	1550	1400	815	279	12.8

RS904



- With 4-U-shaped groove design, the excellent water draining performance and gripping power on wet assured.
- Multiple small tread pattern design improves driving comfort.
- The big tread blocks on shoulder enhance tire strength so that the wear-resistance ability assured and uneven wearing avoided.

Benefits



Comfort



Excellent Handling



Wet Performance



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
P215/75R15	100T	6.0J	5.5J-7.0J	300	800		703	235	8.5
P225/70R15	100H	6.5J	6.0J-7.0J	300	800		697	228	8.5
225/75R15	102T	6.0J	6.0J-7.5J	300	850		719	240	8.5
235/75R15	105T	6.5J	6.0J-8.0J	300	920		733	248	8.5
*255/70R15	108T	7.5J	6.0J-8.0J	250	1000		739	280	8.5
P215/70R16	100H	6.0J	5.5J-7.0J	350	800		708	248	8.5
P225/70R16	103H	6.5J	6.0J-7.5J	350	875		722	260	8.5
*235/60R16	100H	7.0J	6.5J-8.5J	350	800		688	240	8.5
235/70R16	106H	7.0J	6.0J-8.0J	350	950		736	272	8.5
245/70R16	107H	7.0J	6.5J-8.0J	350	975		750	267	8.5
P245/75R16	111T	7.0J	6.5J-8.0J	350	1090		774	221	8.5
P255/70R16	111H	7.5J	6.5J-8.5J	350	1090		764	240	8.5
265/70R16	112H	8.0J	7.0J-9.0J	350	1120		778	248	8.5
P285/75R16	114T	7.5J	6.0J-8.0J	350	1180		804	272	8.5
*275/70R16	114H	8.0J	7.0J-9.0J	350	1180		792	279	8.5
235/65R17	104H	7.0J	6.5J-8.5J	350	900		738	272	8.5
245/65R17	107H	7.0J	7.0J-8.5J	350	975		750	248	8.5
245/70R17	110H	7.0J	6.5J-8.0J	350	1060		776	240	8.5
265/65R17	112H	8.0J	7.5J-9.5J	350	1120		776	248	8.5
265/70R17	115H	8.0J	7.0J-9.0J	350	1215		804	265	8.5
*225/55R18	98V	8.0J	7.0J-9.0J	340	850		737	265	8.5
P235/60R18	107H	7.0J	6.5J-8.5J	340	975		739	240	8.5
245/60R18	105H	7.0J	7.0J-8.5J	300	925		751	265	8.5
255/55R18	105H	8.0J	7.5J-8.5J	300	925		737	265	8.5
245/55R19	103H	7.5J	6.5J-8.5J	300	875		753	284	8.5
255/50R19	107H	8.0J	7.0J-9.0J	340	975		739	273	8.5
255/55R19	107H	8.0J	7.0J-9.0J	300	975		763	267	8.5
275/45R20	110V	9.0J	8.5J-9.5J	340	1060		756	248	8.5
275/55R20	117V	8.5J	7.5J-9.5J	340	1285		810	272	8.5
LT245/75R17-10PR	121/118S	7.0J	6.5J-7.5J	550	1450	1320	800	228	10.5
LT265/70R17-10PR	121/118S	8.0J	7.5J-8.5J	550	1450	1320	804	223	10.5

RS904+



- Adopt zigzag main groove design. Four zigzag wide longitudinal grooves improve the drainage and grasping performance in rainy days.
- Adopt reinforcing rib design, reinforcing rib design increases the rigidity of the pattern block and has the function of cleaning stone.
- the tread end adopts step design to increase the sidewall anti-scratch and anti-friction function.

Benefits



Comfort



Excellent Handling



Wet Performance



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
P215/65R17	99H	6.5J	6.0J-7.0J	300	775		712	221	8.5
235/65R18	106H	7.0J	6.5J-7.5J	300	950		763	240	8.5
265/60R18	110H	8.0J	7.5J-9.5J	300	1060		775	272	8.5
P265/70R18	116H	8.0J	7.5J-8.5J	300	1250		829	272	8.5
P285/60R18	116H	8.5J	8.0J-10.0J	300	1250		799	292	8.5
225/55R19	99V	7.0J	6.5J-7.5J	300	775		731	233	8.5
235/55R19	101V	7.5J	6.5J-8.5J	300	825		741	245	8.5
P285/45R19	111V	9.5J	9.0-10.5J	340	1090		733	289	8.0
P235/45R20	100V	8.0J	7.5-9.0J	340	800		715	240	8.0
235/55R20	105H	7.5J	6.5J-8.5J	340	925		768	245	8.5
245/45R20	103V	8.0J	7.0J-9.0J	340	875		728	243	8.5
P245/50R20	102V	7.5J	7.0J-8.0J	300	850		754	253	8.5
255/45R20	105V	8.5J	8.0J-9.5J	340	925		738	255	8.5
255/50R20	109V	8.0J	7.0J-9.0J	340	1030		764	265	8.5
265/50R20	111V	8.5J	8.0J-9.5J	340	1090		774	277	8.5
P255/55R20	100V	8.0J	7.0-9.0J	340	1060		784	269	8.0
285/50R20	112H	9.0J	8.0J-11.0J	300	1120		794	297	8.5
255/45R21	105T	8.5J	8.0J-9.5J	340	925		763	255	8.5
275/45R21	110V	9.5J	9.0J-10.5J	340	1060		781	273	8.5
275/40R22	107V	9.5J	9.0J-10.5J	340	975		779	278	8.5

RS904A



- With 4-U-shaped groove design, the excellent water draining performance and gripping power on wet assured.
- Multiple small tread pattern design improves driving comfort.
- The big tread blocks on shoulder enhance tire strength so that the wear-resistance ability assured and uneven wearing avoided.

Benefits



Comfort



Excellent Handling



Wet Performance



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
205/75R15	97T	5.5J	5.0J-7.0J	300	730		684	196	8.5
225/75R15	102T	6.0J	6.0J-7.5J	300	850		712.6	221	8.5
235/75R15	105T	6.5J	6.0J-8.0J	300	925		727	236	8.5
255/70R15	108S	7.5J	6.5J-8.5J	300	1000		735	258	8.5
215/65R16	98H	6.5J	6.0J-7.5J	300	750		681	220	8.5
225/75R16	104S	6.0J	6.0J-7.5J	300	900		738	221	8.5
235/70R16	106H	7.0J	6.0J-8.0J	300	950		733	238	8.5
245/70R16	107H	7.0J	6.5J-8.0J	300	975		746	248	8.5
265/70R16	112H	8.0J	7.0J-9.0J	300	1120		772	266	8.5
275/70R16	114H	8.0J	7.0J-9.0J	300	1180		784	272	8.5
215/65R17	99H	6.5J	6.0J-7.5J	300	775		708	222	8.5
225/65R17	102H	6.5J	6.0J-8.0J	300	850		720	233	8.5
235/60R17	102H	7.0J	6.5J-8.5J	300	850		709.4	244	8.5
245/65R17	107H	7.0J	7.0J-8.5J	300	975		744	247	8.5
265/65R17	112H	7.0J	7.5J-9.5J	300	1120		770	268	8.5
265/70R17	115H	8.0J	7.0J-9.0J	300	1215		798	266	8.5
265/60R18	110H	8.0J	7.5J-9.5J	300	1060		770	276	8.5
235/55R19	101V	7.5J	6.5J-8.5J	300	825		736	250	8.5
245/45R20	103V XL	8.0J	7.5J-9.0J	340	875		721	252	8.5
265/50R20	111V XL	8.5J	7.5J-9.5J	340	1090		788.4	286	8.5
275/45R20	110V XL	9.0J	8.5J-10.5J	340	1060		752	276	8.5
275/55R20	117V XL	8.5J	7.5J-9.5J	340	1285		804	286	8.5
285/50R20	112H	9.0J	8.0J-10.0J	300	1120		786	307	8.5
LT235/65R16	120/116S	6.5J	6.0J-7.5J	550	1380	1260	800	224	8.5

RS905



- The balanced void ratio efficiently removes mud and dirt from the tread to provide continuous off-road traction.
- HALUDR mud terrain tire provide traction over various off-road terrain.
- High-tensile steel wires plus nylon reinforced ply, excellent anti-piercing resistance.

Benefits



Wet Performance



Off Road



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
245/75R16LT	120/116 Q	7.0J	6.5J-7.5J	550	1400	1250	780	248	15.5
265/75R16LT	123/120 Q	7.5J	6.0J-7.0J	550	1550	1400	810	267	15.5
265/70R17LT	121/118Q	8.0J	7.5J-8.5J	550	1450	1320	810	272	15.5
285/70R17LT	121/118 Q	8.5J	8.0J-9.0J	550	1450	1320	838	292	15.5
33X12.5R15LT	108 Q	10.0J	9.0J-11.0J	250	1000		832	318	14.5
33X12.5R18LT	118 Q	10.0J	9.5J-10.5J	450	1320		832	318	15.5
33X12.5R20LT	114 Q	10.0J	9.5J-10.5J	450	1180		832	318	15.8
33X12.5R22LT	109 Q	10.0J	9.5J-10.5J	450	1030		832	318	15.5
35X12.5R17LT	119/121Q	10.0J	9.5J-10.5J	350/450	1360/1450		883	318	15.5
35X12.5R18LT	118/123Q	10.0J	9.5J-10.5J	350/450	1320/1550		883	318	15.5
35X12.5R20LT	121 Q	10.0J	9.5J-10.5J	450	1450		883	318	15.5
35X12.5R22LT	117 Q	10.0J	9.5J-10.5J	450	1285		883	318	15.5

RS905+



- The balanced void ratio efficiently removes mud and dirt from the tread to provide continuous off-road traction.
- HALUDR mud terrain tire provide traction over various off-road terrain.
- High-tensile steel wires plus nylon reinforced ply, excellent anti-piercing resistance.

Benefits



Wet Performance



Off Road



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
31*10.50R15LT-8PR	109Q	8.0J	7.0J-9.0J	350	1030		775	288	15.0
33*12.50R17LT-8PR	114Q	10.0J	9.5J-10.5J	450	1400		832	318	15.0
LT235/75R15-6PR	104/101Q	6.5J	5.5J-7.0J	350	900		733	235	15.0
LT285/70R16-10PR	121/118Q	8.0J	7.5J-9.0J	550	1450	1320	779	287	15.0
LT285/75R16-10PR	128/123Q	8.0J	7.5J-9.5J	550	1700	1550	834	286	15.0
LT285/65R17-10PR	120/117Q	8.0J	7.5J-9.5J	550	1550	1400	804	287	15.0

RS906



- Suitable for various premium saloon cars.
- The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Balance of mileage and oil efficiency performance.
- Perfect economy and environmental friendly.

Benefits



Wet Performance



Excellent Handling



Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
155/70R13	75T	4.50B	4.00B-5.00B	250	387		548	157	7.5
155/80R13	79T	4.50B	4.5J-5.00B	300	437		578	157	7.6
165/65R13	77T	5.0J	4.5J-6.0J	300	412		544	170	7.6
165/70R13	79T	5.00B	4.5J-5.0J	300	437		562	170	7.5
165/80R13	83T	4.50B	4.5J-5.00B	300	487		594	165	7.6
175/60R13	77T	5.0J	5.0J-6.0J	300	412		540	177	7.6
175/70R13	82H	5.00B	4.5J-6.0J	300	475		576	177	7.5
185/70R13	86T	5.50B	5.5J-6.00B	250	530		590	189	7.5
155/65R14	75T	4.5J	4.5J-5.5J	300	387		558	157	7.5
165/60R14	75T	5.0J	4.5J-6.0J	270	387		554	170	7.5
165/70R14	85T	5.0J	4.0J-5.5J	300	462		588	170	7.6
175/65R14	86T	5.0J	5.0J-6.0J	300	487		584	177	7.5
175/70R14	84T	5.0J	4.5J-6.0J	300	500		602	177	7.6
175/80R14	88S	5.0J	4.5J-5.5J	240	560		636	171	7.5
185/65R14	86H	5.5J	5.0J-6.5J	300	530		596	189	7.6
185/70R14	88T	5.5J	5.0J-6.0J	300	560		616	189	7.5
185/80R14	91T	5.0J	4.5J-5.5J	300	615		652	184	7.6
195/60R14	86H	6.0J	5.5J-7.0J	300	530		590	201	7.6
195/70R14	91T	6.0J	5.0J-6.0J	300	615		630	201	7.6
205/60R14	88H	6.0J	5.5J-7.5J	300	560		602	209	7.5
205/70R14	93T	6.0J	5.5J-6.5J	300	690		644	209	8.5
175/65R15	88H	5.0J	5.0J-5.5J	300	500		609	177	7.6
185/60R15	84H	5.5J	5.0J-6.5J	300	530		603	189	7.6

RS906



- Suitable for various premium saloon cars.
- The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Balance of mileage and oil efficiency performance.
- Perfect economy and environmental friendly.

Benefits



Wet Performance



Excellent Handling




Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
185/65R15	88H	5.5J	5.0J-6.5J	300	560		621	189	7.5
195/55R15	85V	6.0J	5.5J-7.0J	300	515		595	201	7.5
195/60R15	88V	6.0J	5.5J-7.0J	300	560		615	201	7.5
195/65R15	95H	6.0J	5.5J-7.0J	300	615		635	201	7.5
205/60R15	91H	6.0J	5.5J-7.0J	300	615		627	209	7.5
205/65R15	94H	6.0J	5.5J-7.5J	340	775		647	209	7.6
205/70R15	96T	6.0J	5.0J-7.0J	209	710		669	300	8.4
215/70R15	98T	6.5J	5.5J-7.0J	300	750		683	221	8.7
205/55R16	91W	6.5J	5.5J-7.5J	300	615		632	214	7.5
205/65R16	95H	6.0J	5.5J-7.5J	300	690		672	209	7.6
215/60R16	95H	6.5J	6.0J-7.5J	300	775		664	221	8.0

RS906+



- Suitable for various premium saloon cars.
- The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Balance of mileage and oil efficiency performance.
- Perfect economy and environmental friendly.

Benefits



Wet Performance



Excellent Handling



Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
205/70R14	93T	6.0J	5.5J-7.0J	300	650	644	209	7.7	
185/65R15	88H	5.5J	5.0J-6.5J	350	560	621	189	7.9	
215/60R15	94H	6.5J	6.0J-7.5J	350	670	639	221	7.9	
215/65R15	96H	6.5J	6.0J-7.5J	350	710	661	221	7.9	
205/60R16	92H	6.0J	5.5J-7.5J	340	710	652	209	7.9	
225/60R16	98V	6.5J	6.0J-8.0J	350	750	676	228	7.9	
235/60R16	100H	7.0J	6.5J-8.5J	300	800	688	240	7.9	
225/60R17	99H	6.5J	6.0J-8.0J	350	775	702	228	7.9	

RS906A



- Suitable for various premium saloon cars.
- The innovative central rib design provides excellent steering and grip ability on wet road surface.
- Balance of mileage and oil efficiency performance.
- Perfect economy and environmental friendly.

Benefits



Wet Performance



Excellent Handling



Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
155/70R12	73T	4.50B	4.00B-5.00B	300	365		523	157	7.6
185/60R14	82H	5.5J	5.0J-6.5J	300	475		578	189	7.2
185/70R14	88T	5.5J	5.0J-6.0J	300	560		616	189	7.2

RS907



- Outside strong blocks design enables the tyre to follow the road's surface more closely, helps to reduce blocks deformation while speed coming, and enhances steering precision & better grip.
- Inside wide rib grooves ensures effective water dispersion. Sequential blocks design improves tread rib hardness, enhances braking performance.
- Wide rib grooves effectively removes water, provides shorter braking distances and safer handling on wet roads.
- Racing compound technology provides superior grip performance on wet road surfaces.

Benefits



Comfort



Excellent Handling



Wet Performance



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
145/70R12	69S	4.50B	4.00B-5.00B	250	325		509	150	7.5
155/70R12	73T	4.50B	4.00B-5.00B	300	365		523	157	7.6
175/70R12	80T	5.00B	4.50B-5.00B	300	450		551	177	7.6
155/70R13	75T	4.50B	4.00B-5.00B	250	387		548	157	7.5
165/70R13	79T	5.00B	4.5J-5.0J	300	437		562	170	7.5
165/75R13	83S	4.50B	4.00B-5.00B	250	487		578	165	7.5
175/70R13	82S	5.00B	4.5J-6.0J	300	475		576	177	7.5
185/70R13	86T	5.50B	5.5J-6.00B	250	530		590	189	7.5
155/65R14	75H	4.5J	4.5J-5.5J	300	387		558	157	7.5
165/60R14	75T	5.0J	4.5J-6.0J	270	387		554	170	7.5
165/65R14	79H	5.0J	4.5J-6.0J	300	437		570	170	7.5
175/65R14	82T	5.0J	5.0J-6.0J	300	487		584	177	7.5
185/60R14	82H	5.5J	5.0J-6.5J	300	487		578	189	7.5
185/65R14 XL	90S	5.5J	5.0J-6.5J	300	600		596	189	7.5
185/70R14	88H/T	5.5J	5.0J-6.0J	300	560		616	189	7.5
195/70R14 XL	95H	6.0J	5.0J-6.0J	300	690		630	201	7.5
205/60R14	88H	6.0J	5.5J-7.5J	300	560		602	209	7.5
215/70R14	96H	6.5J	6.0J-7.5J	300	710		658	221	7.5
185/60R15 XL	88H	5.5J	5.0J-6.5J	340	560		603	189	7.5
185/65R15	88H	5.5J	5.0J-6.5J	300	560		621	189	7.5
195/50R15	82V	6.0J	5.5J-6.5J	300	475		577	201	7.5
195/55R15	85V	6.0J	5.5J-7.0J	300	515		595	201	7.5
195/60R15	88H	6.0J	5.5J-7.0J	300	560		615	201	7.5
195/65R15	91H	6.0J	5.5J-7.0J	300	615		635	201	7.5
205/60R15	91H	6.0J	5.5J-7.0J	300	615		627	209	7.5
205/65R15	94H	6.0J	5.5J-7.0J	300	670		647	209	7.5
195/60R16 XL	89H	6.0J	5.5J-6.5J	300	580		640	201	7.5
195/60R16 XL	93H	6.0J	5.5J-6.5J	340	650		640	201	7.5
205/55R16	91V	6.5J	5.5J-7.5J	300	615		632	214	7.5

RS907+



- Outside strong blocks design enables the tyre to follow the road's surface more closely, helps to reduce blocks deformation while speed cornering, and enhances steering precision & better grip.
- Inside wide rib grooves ensures effective water dispersion. Sequential blocks design improves tread rib hardness, enhances braking performance.
- Wide rib grooves effectively removes water, provides shorter braking distances and safer handling on wet roads.
- Racing compound technology provides superior grip performance on wet road surfaces.

Benefits



Comfort



Excellent Handling



Wet Performance



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
155/65R13	73T	4.5J	4.5J-5.5J	300	365		532	157	7.5
175/60R13	77T	5.0J	4.5J-6.0J	300	412		540	177	7.7
185/70R13	86T	5.0B	5.5J-6.00B	350	530		590	189	7.7
165/65R14	79H	5.0J	4.5J-6.0J	350	537		570	170	7.7
165/70R14	85T	5.0J	4.0J-5.5J	340	515		588	170	7.7
175/60R14	79H	5.0J	4.0J-5.5J	300	437		566	177	7.7
175/70R14	84T	5.0J	4.5J-6.0J	350	500		602	177	7.7
185/65R14	86H	5.5J	5.0J-6.5J	350	530		596	189	7.7
195/70R14	91T	6.0J	5.0J-6.0J	350	615		630	201	7.7
175/70R14C-8PR	95/93S	5.0J	4.5J-5.5J	375	690	650	602	177	8.2

RS908



- Optimized groove design to reduce the pattern noise.
- High wear-resistant tread compound to improve tire mileage.
- Four lines tread pattern brings superior handling stability.

Benefits



Longer Mileage



Quiet



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
6.50R16-10PR	107/103N	4.50F	4.5-6.0F	550	975	875	748	174	10.0
7.00R16-10PR	110/107N	4.50F	5.0-6.5F	550	1090	975	770	184	10.0
7.50R16-10PR	116/112N	6.00G	5.5-7.0G	550	1250	1120	801	202	10.0

RS909



- Optimum water dispersion and steering on both sides and minimum rolling resistance with the four long tread grooves and fuzzy pattern.
- Maximum grip and road adhesion with the pattern block and rib pattern on shoulders.
- Strong rim-protecting ring to avoid impact for safe driving at high speed.

Benefits




Comfort



Quiet

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
*185/55R14	80V	6.0J	5.5J-7.5J	280	450		580	194	8.0
*185/55R15	86V	6.0J	5.0J-6.5J	300	475		585	194	8.0
*195/45R15	78V	6.5J	6.0J-7.5J	300	425		557	195	8.0
*195/45R16	84V	6.5J	6.0J-7.5J	300	450		582	195	8.0
215/45ZR16	90W XL	7.0J	7.0J-8.0J	340	600		595	218	8.0
205/45ZR17	88W XL	7.0J	6.5J-7.5J	340	560		611	210	8.0
205/55R17	95V XL	6.5J	5.5J-7.5J	340	690		653	222	8.0
215/50R17	95W XL	7.0J	6.0J-7.5J	340	690		643	237	8.0
225/45ZR17	91W	7.5J	7.0J-8.5J	300	615		628	234	8.0
225/50ZR17	98W XL	7.0J	6.0J-8.0J	340	750		658	233	8.0
225/55R17	101W XL	7.0J	6.0J-8.0J	340	825		675	240	8.0
235/45ZR17	97W XL	8.0J	7.5J-9.0J	340	730		640	244	8.0
245/45ZR17	99W XL	8.0J	7.5J-9.0J	340	775		646	248	8.0
*215/35ZR18	84W	7.5J	6.5J-8.5J	350	500		607	218	8.0
225/40ZR18	92W XL	8.0J	7.5J-9.0J	340	630		630	235	8.0
225/50R18	99W XL	7.0J	6.0J-8.0J	340	775		679	244	8.0
235/50R18	97V	7.5J	6.5J-8.5J	300	730		688	254	8.0
245/40ZR18	97W XL	8.0J	8.0J-9.5J	340	730		647	257	8.0
255/45ZR18	103W XL	8.5J	8.0J-9.5J	340	875		682	264	8.0
245/40ZR19	98W XL	8.5J	8.0J-9.5J	340	750		674	256	8.0
*225/30ZR20	85W	8.0J	7.5J-9.0J	350	515		644	230	8.0
*245/45ZR20	103W	8.0J	7.5J-9.0J	340	875		728	243	8.0
*275/45ZR20	110W	9.0J	8.5J-10.5J	290	1060		756	273	8.0
*285/50R20	116W	9.0J	8.0J-10.0J	350	1250		794	297	8.0
*265/40ZR22	106W	9.5J	9.0J-10.5J	340	950		771	271	8.0
*305/35ZR24	112W	11.0J	10.0J-11.5J	350	1120		824	313	8.0

RS916



- Safety with wide tapered groove pattern applicable to all weather and various road conditions. Better country-crossing capability with its gripping power and anti-skid performance on wet roads.
- Outstanding performance with high-strength steel cord and cap ply.
- Tranquility with fuzzy arrangement of pattern block without specified peak and with variable sound frequency blocks.
- Better loading capacity and anti-shocking performance with reinforced carcass.

Benefits



Comfort



Powerful Traction



Mixed Surface

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
205/70R15	96H	6.0J	5.0J-7.0J	300	710		669	209	8.4
215/75R15	100T	6.0J	5.5J-7.0J	300	800		703	216	8.4
P215/75R15	100S	6.0J	5.5J-7.0J	250	800		703	216	8.4
225/75R15	102S	6.0J	5.5J-6.5J	250	850		719	223	8.4
235/75R15 XL	109T	6.5J	6.0J-8.0J	300	1030		733	235	8.7
235/75R15	105S	6.5J	6.0J-8.0J	260	925		733	235	8.7
LT235/75R15-6PR	104/101S	6.5J	6.0J-7.0J	300	900	825	733	235	8.7
31X10.5R15LT-6PR	109Q	8.5J	8.0J-9.0J	300	1030		775	268	8.7
215/70R16	100H	6.5J	5.5J-7.0J	300	800		708	221	8.7
225/70R16	103T	6.5J	6.0J-7.5J	340	875		722	228	8.7
235/70R16	106T	7.0J	6.0J-8.0J	300	950		736	240	8.4
245/70R16 XL	111S	7.0J	6.5J-8.0J	300	1090		750	248	8.4
245/75R16	111T	7.0J	6.5J-8.0J	300	1090		774	248	8.4
265/70R16	112T	8.0J	7.0J-9.0J	300	1120		778	272	8.4
265/75R16	116S	7.5J	7.0J-9.0J	300	1250		804	267	8.4
275/70R16	114H	8.0J	7.5J-9.5J	340	1180		792	279	8.8
215R16C-6PR	109/107Q	6.0J	5.5J-6.5J	300	1060	1000	750	218	8.8
245/75R16LT	120/116Q	7.0J	6.5-7.5J	300	1380	1260	774	248	8.8
235/60R17	102H	7.0J	6.5J-8.5J	350	850		714	240	8.4
235/65R17 XL	108T	7.0J	6.5J-8.5J	350	1000		738	240	11.5
265/65R17	112H	8.0J	7.5J-9.5J	375	1120		776	272	8.4
275/65R17	115T	8.0J	7.5J-9.5J	550	1215		790	279	8.4
235/65R16LT	120/116S	6.5J	6.0J-7.5J	550	1400		806	235	8.5

RS920



- For wide longitudinal water-escaping grooves and spacious transverse water-escaping grooves water to improve water dispersion for excellent traction and braking on wet roads. Powerful with the luxurious SUV-oriented UHP tyre.
- Outstanding performance on all roads with the wide tread and high groove-sipe ratio.
- Tranquil ride with the ideal pitch design and the variable sound frequency blocks.
- Special quality with good performance on anti-puncture, underlay-damage and anti-fracture from the unique sidewall protection layer.

Benefits



Wet Performance



Excellent Handling



Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (kPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
P205/70R15	96H	6.0J	5.5J-7.0J	280	710		669	209	8.0
P215/75R15	100S	6.0J	5.5J-7.0J	250	800		703	216	8.0
P235/75R15	105S	6.5J	6.0J-7.5J	260	925		733	235	8.0
P245/70R16	107S	7.0J	6.0J-8.0J	300	975		750	248	8.4
P265/70R16	112S	8.0J	7.5J-9.0J	260	1120		778	272	8.4
P265/75R16	116S	7.5J	6.0J-8.0J	260	1250		804	267	8.4
P265/65R17	112S	8.0J	7.5J-9.5J	260	1120		776	272	8.4

RS922



- Asymmetric pattern, big shoulder block, excellent control on dry road, wide grooves helps excellent water drainage.
- Wide lateral grooves design helps improve the performance of drainage and wet grip.
- Central steel block, speeds more quickly, controls more accurately.

Benefits



Wet Performance



Excellent Handling



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
195/55R16	87V	6.0J	5.5J-7.0J	300	545		620	201	8.0
195/60R16	89H	6.0J	5.5J-7.0J	300	580		640	201	8.0
205/45R16	87V	7.0J	6.5J-7.5J	340	545		590	206	8.0
*225/50R16	96V	7.0J	6.0J-8.0J	340	710		632	233	8.0
*255/65R16	109T	7.5J	7.0J-9.0J	350	1030		738	260	8.0
*205/50ZR17	93W	6.5J	6.0J-7.0J	340	650		638	214	8.0
205/55R17	95V	6.5J	5.5J-7.5J	340	670		658	214	8.0
*215/40ZR17	87W	7.5J	7.0J-8.0J	340	545		604	218	8.0
*215/45ZR17	91W	7.0J	6.5J-7.5J	340	615		626	213	8.0
215/50R17	95W	7.0J	6.0J-7.5J	340	690		648	226	8.0
215/60R17	96H	6.5J	6.0J-7.5J	300	710		690	221	8.0
*225/45ZR17	94W	7.5J	7.0J-8.5J	300	615		628	234	8.0
*225/50ZR17	98W	7.0J	6.0J-7.5J	340	750		658	233	8.0
*235/45ZR17	97W	8.0J	7.5J-9.0J	340	730		644	236	8.0
*235/50R17	100V	7.5J	7.0J-8.0J	350	800		688	245	8.0
*235/55R17	103V	7.5J	6.5J-8.5J	300	875		690	245	8.0
245/45R17	99W	8.0J	7.5J-9.0J	340	775		652	243	8.0
*215/40ZR18	89W	7.5J	7.0J-8.5J	340	580		629	218	8.0
*215/45ZR18	93W	7.0J	6.5J-7.5J	340	650		651	213	8.0
215/50R18	92W	7.0J	6.0J-7.5J	300	630		673	226	8.0
215/55R18	99H	7.0J	6.5J-7.5J	340	775		693	226	8.0
*225/40ZR18	92W	8.0J	7.5J-9.0J	340	630		637	230	8.0
*225/45ZR18	95W	7.5J	6.5J-8.5J	350	690		659	225	8.0

RS922



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
225/50R18	99W	7.0J	6.5J-7.5J	340	775		683	233	8.0
225/55R18	98H	7.0J	6.5J-7.5J	300	750		705	233	8.0
225/60R18	100H	6.5J	6.0J-8.0J	300	750		727	228	8.0
*235/40ZR18	95W	8.5J	8.0J-9.0J	300	615		645	241	8.0
235/45ZR18	94W	8.0J	7.5J-8.5J	300	670		669	236	8.0
235/50R18	97V	7.5J	7.0J-8.5J	300	730		693	245	8.0
235/55R18	100V	7.5J	6.5J-8.5J	300	800		715	245	8.0
*235/60R18	103V	7.0J	6.5J-8.5J	340	875		739	240	8.0
*245/40ZR18	97W	8.5J	7.5J-9.5J	350	730		653	248	8.0
*245/45ZR18	100W	8.0J	7.0J-9.0J	350	800		677	243	8.0
245/50R18	104V	7.5J	6.5J-8.5J	340	900		703	253	8.0
255/45R18	103W	8.5J	7.5J-9.5J	340	875		687	255	8.0
*255/55ZR18	109V	8.0J	7.0J-9.0J	340	1030		737	265	8.0
*H265/35ZR18	97W	9.5J	9.0J-10.5J	340	730		643	271	8.0
*265/60R18	110H	8.0J	7.5J-9.5J	350	1060		775	272	8.0
*225/35ZR19	88W	8.0J	7.5J-8.5J	340	560		641	230	8.0
*225/40ZR19	93W	8.0J	7.5J-8.5J	340	650		663	230	8.0
225/45ZR19	96W	7.5J	7.0J-8.0J	340	710		685	225	8.0
235/35ZR19	91W	8.5J	7.5J-9.5J	340	615		647	241	8.0
235/50R19	91W	8.5J	8.0J-9.5J	300	775		719	245	8.0
*235/55R19	105V	7.5J	6.5J-8.5J	350	925		741	244	8.0
*245/35ZR19	93W	8.5J	8.0J-9.5J	350	650		655	248	8.0
*245/40ZR19	98W	8.5J	8.0J-9.5J	340	750		679	248	8.0
245/45ZR19	102W	8.5J	8.0J-9.5J	340	850		703	243	8.0
255/40ZR19	100W	9.0J	8.5J-9.5J	340	800		687	260	8.0
255/45R19	104W	8.5J	8.0J-9.5J	340	900		713	255	8.0
*255/55R19	111V	8.0J	7.0J-9.0J	350	1090		763	265	8.0
*265/30ZR19	93W	9.5J	9.0J-10.0J	340	650		643	271	8.0
*225/35ZR20	93W	8.0J	7.5J-8.5J	350	650		666	230	8.0
*235/30ZR20	88W	8.5J	8.0J-9.5J	340	560		650	242	8.0
*245/35ZR20	95W	8.5J	8.0J-9.5J	300	615		680	248	8.0
*255/35ZR20	102Y	9.0J	8.5J-10.0J	350	850		686	260	8.0
*265/50ZR20	111W	8.5J	8.0J-9.0J	340	1090		774	277	8.0
*265/45ZR21	104W	9.0J	8.5J-10.0J	300	900		771	266	8.0
*295/35ZR21	107W	10.5J	10.0J-11.5J	340	975		739	301	8.0
*265/35ZR22	102W	9.5J	9.0J-10.5J	350	850		745	271	8.0
*275/40ZR22	107W	9.5J	9.0J-10.5J	350	850		745	271	8.0
*285/35ZR22	106W	9.5J	9.0J-10.0J	350	950		788	264	8.0

RS922+



- Asymmetric pattern design provide a strong grip and confident maneuvering and tread even wearing during turning.
- Four wide longitudinal groove design and wide contact patch helps to deliver a high speed performance and excellent water drainage.
- Angular sipes help reduce noise and provide comfortable riding.
- Special tread ingredient design with silicon helps to provide a good grip both on dry adn wet road. Longer mileage.

Benefits



Wet Performance



Excellent Handling



Economy

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
185/55R15	82V	6.0J	5.0J-6.5J	350	475		585	194	7.9
195/50R15	82V	6.0J	5.5J-6.5J	350	475		577	201	7.9
195/50R16	88V	6.0J	5.5J-7.0J	340	560		602	201	7.9
205/50R16	87V	6.5J	5.5J-7.5J	350	545		612	214	7.9
215/55R16	97W	7.0J	6.0J-7.5J	340	730		642	226	7.9
225/55R16	95W	7.0J	6.0J-8.0J	350	690		654	233	7.9
205/40ZR17	84W	7.5J	7.0J-8.0J	350	500		596	212	7.9
205/50R17	93W	6.5J	5.5J-7.5J	340	650		638	214	7.9
215/40ZR17	87W	7.5J	7.0J-8.0J	350	545		604	218	7.9
215/45R17	91W	7.0J	7.0J-8.0J	340	615		626	213	7.9
215/55R17	98W	7.0J	6.0J-7.5J	340	750		668	226	7.9
225/50R17	98W	7.0J	6.0J-8.0J	340	750		658	233	7.9
235/45R17	97W	8.0J	7.5J-9.0J	340	730		644	236	7.9
235/50R17	96W	7.5J	7.0J-8.0J	350	710		668	245	7.9
235/55R17	99W	7.5J	6.5J-8.5J	350	775		690	245	7.9
215/35ZR18	84W	7.5J	6.5J-8.5J	350	500		607	218	7.9
225/45R18	95W	7.5J	7.0J-8.5J	350	690		659	225	7.9
235/40ZR18	95W	8.5J	8.0J-9.0J	350	690		645	241	7.9
245/45R18	100W	8.0J	7.5J-9.0J	350	800		677	243	7.9
245/35R20	95W	8.5J	8.0J-9.0J	340	690		680	248	7.9

RS922A



- Densely distributed blocks efficiently offset noises made by air emission in the grooves.
- Four longitudinal groove design to ensure good drainage performance on wet surface.
- Widen central pattern rib to ensure the handling at the time of intense driving.

Benefits



Wet Performance



Excellent Handling



Quiet

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
225/35ZR20	90W	8.0J	7.0J-9.0J	340	600		666	230	8.0
255/35ZR20	97W	9.0J	8.0-10.0J	340	730		686	260	8.0
275/40ZR20	106W	9.5J	9.0J-10.5J	340	950		728	278	8.0
245/30ZR22	92W	8.5J	8.0J-9.5J	340	630		707	248	8.0
265/35R22	102V	9.5J	9.0J-10.5J	340	850		745	271	8.0
305/40R22	114V	11.0J	10.0J-11.5J	340	1180		803	313	8.0
305/45R22	118V	10.0J	9.5J-10.5J	340	1320		833	303	8.0

RS922A+



- Adopt sports profile with maximum rigidity and aggressive appearance.
- Big shoulder block pattern with big sipes can avoid uneven wear and dffectively reduce the heating up and resonance.
- Asymmetric tread design and low rolling resistance provides excellent handling performance and outstanding driving properties on dry & wet road surfaces.

Benefits



Wet Performance



Excellent Handling

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
265/30ZR22	97W	9.5J	9.0J-10.5J	340	730		719	271	8.0
265/40R22	106V	9.5J	9.0J-10.5J	340	950		771	271	8.0
285/35ZR22	106W	10.0J	9.5J-10.5J	340	950		759	290	8.0
305/35R24	112V	11.0J	10.0J-11.5J	340	1120		824	313	8.0

RS928



- New formula reduces 30%-40% of rolling resistance, decreases fuel consumption and CO2 emission load.
- Wide tread design increase road contact area, maintains safe ride, and enhances wear-resisting performance.
- High ratio straight main sipes design effectively reduces rolling resistance and noise, perfectly combines environmental protection with comfort.
- Pitching sequence shoulder blocks design shows outstanding controlling at high speed. Perfect distribution of lug type pattern with thin sipes in the tread enhances traction on wet roads.

Benefits



Wet Performance



Excellent Handling



Comfort



Longer Mileage

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
175/70R12	80H	5.00B	4.50B-5.00B	300	450		551	177	7.6
155/65R14	75T	4.5J	4.5J-5.5J	300	387		532	157	7.6
175/65R14	82T	5.0J	5.0J-6.0J	300	475		584	177	7.6
175/70R14	84T	5.0J	4.5J-6.0J	300	500		602	177	7.6
195/70R15	92S	6.0J	5.5J-7.0J	300	630		655	201	7.6
205/70R15	96H	6.0J	5.5J-7.0J	300	710		669	209	7.6
215/70R15	98H/T	6.5J	5.5J-7.0J	300	750		683	221	7.6
225/75R15	102S	6.0J	5.5J-7.0J	300	850		719	223	7.6
195/50R16	84V	6.0J	5.5J-7.0J	300	500		602	201	7.6
205/50R16 XL	91V	6.5J	5.5J-7.5J	340	615		612	214	7.6
205/55R16	91V	6.5J	5.5J-7.5J	300	615		632	214	7.6
205/60R16	92H	6.0J	5.5J-7.5J	300	630		652	209	7.6
205/65R16	95H	6.0J	5.5J-7.5J	300	690		672	209	7.6
215/60R16 XL	99H	6.5J	5.5J-7.5J	340	775		664	221	7.6
215/65R16	98H	6.5J	6.0J-7.0J	300	750		686	221	7.6
225/60R16	98H	6.5J	6.0J-8.0J	300	750		676	228	7.6
205/55R17	91H	6.5J	5.5J-7.5J	350	615		657	216	7.6
215/55R17	94H	7.0J	6.0J-8.0J	300	670		688	226	7.6
215/60R17	96H	6.5J	6.0J-8.0J	300	710		690	221	7.6
215/65R17	99V	6.5J	5.5J-7.5J	300	775		710	221	7.6
225/55R17	87V	7.0J	6.0J-8.0J	300	545		680	233	7.6
225/60R17	99H	6.5J	6.0J-8.0J	300	775		702	228	7.6
225/65R17	102H	6.5J	6.0J-8.0J	300	850		724	221	7.6
225/60R18	100V	6.5J	6.0J-8.0J	300	800		728	228	7.6
235/50R18 XL	101V	7.5J	7.0J-8.0J	340	825		693	245	7.6

RS930



- The wide design and pattern with new 3D saw tooth style fine sipe greatly improved the grasp area of the tread and effectively increased the grasp force of the tire on ice and snow.
- The Strong longitudinal ribbed pattern blocks greatly improve the snow grip of tires.
- The materials such as silica etc are added in the tread compound; it is low-temperature resistance and features excellent adhesion force on the ice/snow.

Benefits



Powerful Traction



Comfort



Snow Performance

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
165/70R13	83Q/T	5.00B	4.50B-5.00B	340	487		562	170	8.0
175/70R13	82T	5.0J	4.5J-5.5J	300	475		576	177	8.0
165/70R14	81T	5.0J	4.5J-6.0J	300	462		588	170	8.0
175/70R14	84Q/T	5.0J	4.5J-6.0J	300	500		602	177	8.0
175/65R14	82Q/T	5.0J	5.0J-6.0J	300	475		584	177	8.0
185/60R14	82Q/T	5.5J	5.0J-6.0J	300	475		578	189	8.0
185/65R14	90Q/T	5.5J	5.0J-6.0J	340	600		596	189	8.0
195/60R14	86Q	6.0J	5.5J-7.0J	300	530		590	201	8.0
185/60R15	84Q/T	5.5J	5.0J-6.0J	300	500		603	189	8.0
185/65R15	88Q/T	5.5J	5.0J-6.0J	300	560		621	189	8.0
195/55R15	85T	6.0J	5.5J-7.0J	300	515		595	201	8.0
195/60R15	88Q/T	6.0J	5.5J-7.0J	300	560		615	201	8.0
195/65R15	91Q/T	6.0J	5.5J-7.0J	300	615		635	201	8.0
205/65R15	94T	6.0J	5.5J-7.0J	300	670		647	209	8.0
215/70R15	98H	6.5J	6.0J-7.0J	300	750		683	221	8.0
235/75R15	105Q	6.5J	6.0J-7.0J	300	925		733	235	8.0
195/55R16	91H	6.0J	6.0J-7.0J	340	615		620	201	8.0
205/55R16	91Q/T	6.5J	6.0J-7.0J	300	615		632	214	8.0
205/60R16	96T	6.0J	5.5J-7.0J	340	710		652	209	8.0
215/55R16	97T	7.0J	6.0J-8.0J	340	730		642	226	8.0
215/60R16	95Q/T	6.5J	6.0J-7.0J	300	690		664	221	8.0
215/65R16	98Q/T	6.5J	6.0J-7.0J	300	750		686	221	8.0
215/70R16	100Q	6.5J	6.0J-7.0J	300	800		708	221	8.0
225/55R16	99T	7.0J	6.0J-8.0J	340	775		654	223	8.0
225/60R16	102Q/T	6.5J	6.0J-7.0J	340	850		676	228	8.0

RS930



- The wide design and pattern with new 3D saw tooth style fine sipe greatly improved the grasp area of the tread and effectively increased the grasp force of the tire on ice and snow.
- The Strong longitudinal ribbed pattern blocks greatly improve the snow grip of tires.
- The materials such as silica etc are added in the tread compound; it is low-temperature resistance and features excellent adhesion force on the ice/snow.

Benefits



Powerful Traction



Comfort



Snow Performance

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
226/65R16	100T	6.5J	6.0J-7.0J	300	800		698	228	8.0
235/70R16	106Q	7.0J	6.0J-8.0J	300	950		736	240	8.0
215/45R17	91V	7.0J	6.0J-8.0J	340	615		626	213	8.0
215/50R17	95Q/H	6.5J	6.0J-7.0J	340	690		638	214	8.0
215/55R17	95Q/H	7.0J	6.0J-8.0J	300	670		668	226	8.0
215/60R17	96T	6.5J	6.0J-7.0J	300	710		690	221	8.0
225/55R17	101H	7.0J	6.0J-8.0J	340	825		680	233	8.0
225/60R17	99T	6.5J	6.0J-7.0J	300	775		702	228	8.0
225/65R17	102Q/T	6.5J	6.0J-7.0J	300	850		724	228	8.0
225/45R17	94H	7.5J	7.0J-8.0J	340	670		634	225	8.0
235/45R17	97H	8.0J	7.5J-9.0J	340	730		644	236	8.0
235/55R17	99T	7.5J	7.0J-8.0J	300	775		690	245	8.0
235/65R17	104T	7.0J	6.0J-8.0J	300	900		738	240	8.0
265/65R17	112T	8.0J	7.5J-9.0J	300	1120		776	272	8.0
265/70R17	115T	8.0J	7.5J-9.0J	300	1215		810	272	8.0
275/65R17	115T	8.0J	7.5J-9.0J	300	1215		790	279	8.0
225/45R18	95Q/H	7.5J	7.0J-8.0J	350	690		659	225	8.0
225/40R18	92H	8.0J	7.5J-9.0J	340	630		637	230	8.0
235/55R18	104T	7.5J	7.0J-8.0J	340	900		715	245	8.0
235/60R18	103T	7.0J	6.0J-8.0J	300	875		739	240	8.0
245/40R18	93H	8.5J	8.0J-9.5J	340	730		653	248	8.0
245/45R18	100V	8.0J	7.5J-9.0J	350	800		677	243	8.0
275/65R18	116T	8.0J	7.5J-9.0J	300	1250		815	279	8.0
275/55R20	117T	8.5J	8.0J-9.5J	340	1285		810	284	8.0
275/60R20	115T	8.0J	7.5J-9.0J	300	1215		844	279	8.0

RS931



- Special pattern design with high density jag sipes make sure the good grip and brake performance snow or ice covered road.
- Four longitudinal grooves design for excellent water drainage and good handling.
- Apply for computer and gene combination simulation design, have the best pattern noise combination, improve vehicle comfort.
- Special snow tyre compound and structure design.

Benefits



Wet Performance



Comfort



Snow Performance



Powerful Traction

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
155/65R13	73Q	4.50B	4.00B-5.00B	300	365		532	157	8.8
165/70R13	79Q	5.00B	4.50B-5.00B	350	437		562	170	8.0
175/70R13	82Q	5.00B	4.50B-5.00B	300	475		576	177	8.8
165/60R14	75S	5.0J	5.0J-6.0J	300	387		554	170	8.8
175/75R14	82Q	5.0J	5.0J-6.0J	300	475		584	177	8.8
175/70R14	84Q	5.0J	5.0J-6.0J	300	500		602	177	9.0
185/60R14	82Q	5.5J	5.0J-6.0J	350	475		578	189	8.0
185/65R14	86S	5.5J	5.0J-6.0J	300	530		596	189	9.0
185/70R14	88S	5.5J	5.0J-6.0J	300	560		616	189	8.0
195/60R14	86Q	6.0J	5.5J-6.5J	350	530		590	201	8.0
175/65R15	84Q	5.0J	5.0J-6.0J	300	500		609	177	8.8
185/60R15	84S	5.5J	5.0J-6.0J	300	500		603	189	9.0
185/65R15	88Q	5.5J	5.0J-6.0J	350	560		621	189	8.0
195/55R15	85Q	6.0J	5.5J-6.5J	350	515		595	201	8.0
195/60R15	88Q	6.0J	5.5J-6.5J	350	560		615	201	8.0
195/65R15	91Q	6.0J	5.5J-6.5J	350	615		635	201	8.0
205/65R15	94S	6.0J	5.5J-6.5J	300	670		647	209	9.0
215/75R15	100Q	6.0J	5.5J-6.5J	300	800		703	216	9.0
195/60R16	89S	6.0J	5.5J-6.5J	300	580		640	201	9.0
205/55R16	91Q	6.5J	6.0J-7.0J	350	615		632	214	8.0
205/60R16	92S	6.0J	5.5J-6.5J	300	630		652	209	9.0
215/55R16	93S	7.0J	6.5J-7.5J	300	650		642	226	9.0
215/60R16	95Q	6.5J	6.0J-7.0J	300	690		664	221	9.0
215/70R16	100S	6.5J	6.0J-7.0J	300	800		708	221	9.0
225/70R16	103S	6.5J	6.0J-7.0J	300	875		722	228	9.0
215/60R17	96S	6.5J	6.0J-7.0J	300	710		690	221	9.0
225/65R17	102Q	6.5J	6.0J-7.0J	300	850		724	228	9.0
265/65R17	112S	8.0J	7.5J-9.5J	300	1120		776	272	9.2
235/60R18	103Q	7.0J	6.5J-7.5J	300	875		739	240	9.0
195/70R15C	104/102Q	6.0J	5.5J-6.5J	450	900	850	655	201	10.0

RS932



- Special pattern design with high density sawtooth lateral groove, make sure excellent grip and brake performance on snow or ice covered road.
- Wider pattern design on inner side of shoulder to achieve better traction on snow road.
- With hundreds of tiny grooves on the tread, fabulous ability to absorb water to refrain aquaplaning.
- Brand new 3D pattern designing, 20% more space inside of the groove enhanced mutual support between pattern blocks, better grip performance.

Benefits



Wet Performance



Comfort



Snow Performance



Powerful Traction

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
205/65R16	95T	6.0J	5.5J-6.5J	300	690		672	209	8.5
225/55R16	95T	7.0J	6.5J-7.5J	300	690		654	233	8.5
205/50R17	93H	6.5J	6.0J-7.0J	300	650		638	214	8.5
205/55R17	95T	6.5J	6.0J-7.0J	340	690		658	214	8.5
215/45R17	91H	7.0J	6.5J-7.5J	340	615		626	213	8.5
215/50R17	95H	7.0J	6.5J-7.5J	340	690		684	226	8.5
215/55R17	94T	7.0J	6.5J-7.5J	300	670		668	226	8.5
225/45R17	964H	7.5J	6.0J-8.0J	340	670		634	225	8.5
225/50R17	94T	7.0J	6.5J-7.5J	300	670		658	233	8.5
225/55R17	97H	7.0J	6.5J-7.5J	300	730		680	233	8.5
235/45R17	97S	8.0J	7.5J-9.5J	300	730		644	236	8.5
235/55R17	99S	7.5J	6.0J-8.0J	340	775		690	245	8.5
215/50R18	92T	7.0J	6.5J-7.5J	340	630		673	226	8.5
215/55R18	99H	7.0J	6.5J-7.5J	300	775		693	226	8.5
225/40R18	92H	8.0J	7.5J-9.5J	340	630		637	230	8.5
225/45R18	95H	7.5J	6.0J-8.0J	340	690		659	225	8.5
225/50R18	99H	7.0J	6.5J-7.5J	340	775		683	233	8.5
235/45R18	98T	8.0J	7.5J-9.5J	340	750		669	236	8.5
235/50R18	101H	7.5J	6.0J-8.0J	340	825		693	245	8.5
235/55R18	100H	7.5J	6.0J-8.0J	340	800		715	245	8.5
245/40R18	97H	8.5J	7.0J-9.0J	340	730		653	248	8.5
245/45R18	96S	8.0J	7.5J-9.5J	340	710		677	243	8.5
245/50R18	104H	7.5J	6.0J-8.0J	340	900		703	253	8.5
255/40R18	99S	9.0J	8.5J-9.5J	300	775		661	260	8.5
255/45R18	103T	8.5J	7.0J-9.0J	300	875		713	255	8.5

RS933



- Multiple combination of pattern groove designing, enhance grip ability, safeguard the driving in winter.
- Special pattern design with high density sawtooth lateral groove, make sure excellent grip and brake performance on snow or ice covered road.
- Brand new 3D pattern designing, 20% more space inside of the groove enhanced mutual support between pattern blocks, better grip performance.

Benefits



Wet Performance



Comfort



Snow Performance



Powerful Traction

Vehicle



Tire Size	LI&SR	Measure Rim	Alternative Rim	Pressure (KPa)	Single Load(Kg)	Dual Load(Kg)	OD(mm)	SW(mm)	Tread Depth(mm)
285/70R16	112T	8.0J	7.5J-9.5J	340	710		685	225	10.5
215/65R16	98S	6.5J	6.0J-8.0J	300	750		686	221	10.0
235/70R16	106S	7.0J	6.5J-8.5J	300	950		736	240	10.5
225/60R17	99S	6.5J	6.0J-8.0J	300	775		702	228	10.0
235/65R17	104T	7.0J	6.5J-8.5J	300	900		738	240	10.0
245/65R17	107S	7.0J	6.5J-8.5J	300	975		750	248	10.5
215/65R17	99T	6.5J	6.0J-8.0J	300	775		712	221	10.0
225/55R18	98S	7.0J	6.5J-8.5J	300	950		705	233	10.0
225/60R18	100S	6.5J	6.0J-8.0J	300	800		727	228	10.0
245/60R18	105T	7.0J	6.5J-8.5J	300	925		751	248	10.5
265/60R18	110R	8.0J	7.5J-9.5J	300	1060		775	272	10.5
235/65R18	106T	7.0J	6.5J-8.5J	300	950		763	240	10.5
255/60R18	112T	7.5J	6.0J-8.0J	340	1120		763	260	10.5
225/45R19	96T	7.5J	6.0J-8.0J	340	710		685	225	10.5
225/55R19	99T	7.0J	6.5J-8.5J	300	775		731	233	10.0
245/55R19	103R	7.5J	6.0J-8.0J	300	875		753	253	10.5
235/50R19	99T	7.5J	6.0J-8.0J	300	775		719	245	10.0
245/45R19	102T	8.0J	7.5J-9.5J	340	850		703	243	10.5
255/55R19	107T	8.5J	7.0J-9.0J	300	975		763	265	10.5
255/45R19	100T	9.5J	9.0J-10.0J	300	800		713	255	10.5
275/40R19	105T	8.5J	7.0J-9.0J	340	925		703	278	10.5
265/50R19	110T	7.5J	6.0J-8.0J	340	1060		749	277	10.5
235/55R19	101T	9.0J	8.5J-9.5J	300	825		741	245	10.0
255/40R19	100T	9.0J	8.5J-9.5J	340	800		687	260	10.5
275/45R20	106S	7.5J	6.0J-8.0J	300	950		756	273	10.5
235/55R20	102T	7.5J	6.0J-8.0J	300	850		766	245	10.5
245/60R120	102T	8.0J	7.5J-9.5J	300	850		754	253	10.5
255/50R20	109S	8.5J	7.0J-9.0J	340	1030		764	265	10.5
275/55R20	117S	9.0J	8.5J-9.5J	340	1285		810	284	10.5
285/50R20	112S	8.0J	7.5J-9.5J	300	1120		794	279	10.5
245/45R20	103T	9.0J	8.5J-9.5J	340	875		728	243	10.5
275/45R21	110T	9.0J	8.5J-9.5J	340	1060		781	273	10.0
255/45R21	105T	8.5J	7.0J-9.0J	340	925		763	255	10.5
275/40R22	107T	9.5J	9.0J-10.0J	340	975		779	278	10.5

225/40ZR18 92W XL TUBELESS

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- | | |
|--------------------------------------|-------------------------|
| 1. Tire width | 6. Load Index |
| 2. Tire aspect ratio | 7. Speed range |
| 3. Tire speed range exceeds 240km/h | 8. Extra Load indicator |
| 4. Radial tire (tire structure type) | 9. Tubeless type |
| 5. Tire inner diameter (inch) | |

Speed Symbols and Maximum Speed

SI	L	M	N	P	Q	R	S	T	U	H	V	W	Y
Km/H	120	130	140	150	160	170	180	190	200	210	240	270	300

Loading Capacity Index

LI	Kg	LI	Kg	LI	Kg	LI	Kg
55	218	79	439	101	825	123	1550
58	218	80	450	102	850	124	1600
59	243	81	462	103	875	125	1650
60	250	82	485	104	900	126	1700
61	257	83	487	105	925	127	1750
62	265	84	500	106	950	128	1800
63	272	85	515	107	975	129	1850
64	280	86	530	108	1000	130	1900
65	290	87	545	109	1030	131	1950
66	300	88	560	110	1060	132	2000
67	307	89	580	111	1090	133	2060
68	315	90	600	112	1120	134	2120
69	325	91	615	113	1150	135	2180
70	335	92	630	114	1180	136	2240
71	345	93	650	115	1215	137	2300
72	355	94	670	116	1250	138	2360
73	365	95	690	117	1285	139	2430
74	375	96	710	118	1320	140	2500
75	387	97	730	119	1360		
76	400	98	750	120	1400		
77	412	99	775	121	1450		
78	425	100	800	122	1500		

HONGTYRE INTERNATIONAL FZE

Add: NO.43 Bangkok Road, Qingdao Free Trade Zone, Qingdao, China.

Tel: +86-532- 86766013 +86-532- 86768126

+86-532- 86768852 +86-532- 86766033

+86-532- 86768057 +86-532- 86768067

+86-532- 86768860 +86-532- 86768065

Fax: +86-532-86769930

Email: roadshine@hongtyre.com;

Web:www.hongtyre.com;