



ROADSHINE *pro*

TRUCK & BUS RADIAL TYRES



CONTENTS

RS601A	-----	01
RS601AA	-----	02
RS602A	-----	03
RS604	-----	04
RS606A	-----	05
RS606A+	-----	06
RS608AA	-----	07
RS609A+	-----	08
RS612A	-----	09
RS612AA	-----	10
RS617AA	-----	11
RS618+	-----	12
RS618A	-----	13
RS618AA	-----	14
RS619A	-----	15
RS620A	-----	16
RS621A	-----	17
RS622	-----	18
RS630	-----	19
RS630+	-----	20
RS630A	-----	21
RS630A+	-----	22
RS631A	-----	23
RS631AA	-----	24
RS637AA	-----	25

RS601A



- Three main grooves and two block type ribs on the tread center provide good traction on wet and dry road conditions.
- Special anti-cut tread compound provides high resistance for cut and chipping.
- Easy handling.
- Tough belt construction for smooth tread wear.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	12.00	236
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1054	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	16.50	346
12.00R20	20	J	156/153	8.50	4000	3650	900	900	315	1125	16.50	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1226	15.00	372

RS601AA



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	20	K	148/145	8.25	3150	2900	850	850	279	1056	17.50	320
12R22.5	22	K	152/149	9.00	4250	4000	900	900	300	1078	17.50	343
295/80R22.5	22	K	154/149	9.00	3750	3250	850	850	298	1049	17.50	335
315/70R22.5	20	K	156/150	9.00	4000	3350	900	900	314	1018	18.00	351
315/80R22.5	22	K	158/156	9.00	4250	4000	900	900	300	1078	17.50	351
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	17.50	318

RS602A



- Unique three fold line pattern with excellent traction performance and antiwear biased characteristics.
- Four rigid belt layer, with excellent resistance to blast resistance and piercing ability.
- Optimizing tire ground pressure distribution, prolong the tyre life.
- Designed for heavy duty, middle and long distance road, high-speed in good road, suitable for all wheels of a truck.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
6.50R16LT	10	L	107/102	5.50F	975	850	560	560	185	750	10.50	220
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	12.00	236
7.50R16LT	14	K	122/118	6.00G	1500	1320	770	770	215	805	13.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50H	2430	2300	930	930	236	974	15.00	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1019	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1054	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	20	K	158/153	8.50	4000	3650	900	900	315	1125	17.50	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1226	17.50	372
11R22.5	18	L	149/146	8.25	3250	3000	930	930	279	1054	17.50	320
12R22.5	18	L	142/149	9.00	3550	3250	930	930	300	1085	17.00	343
315/80R22.5	20	L	157/154	9.00	4125	3750	900	900	312	1076	18.00	351

RS604



- Drive wheel application.
- Mainly for regional and medium haul on mixed road condition.
- Directed and mixed pattern with strengthening rib for good drive and brake performance.
- Deep tread to extend tire service life.
- Improved carcass in structure design for good carrying capacity.

Benefits




Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
1200R24	20	K	160/157	8.50	4500	4125	900	900	315	1226	19.00	372
325/65R24	22	K	162/160	9.00	4750	4500	850	850	325	1228	19.50	372

RS606A



- Aggressive lug tread for powerful grip on or off the road.
- Deep original tread for long life and outstanding traction.
- Special tread compounds help resist cuts, chips, tearing and irregular wear.

Benefits



Off Road




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	J	152/149	8.00	3550	3250	930	930	293	1085	20.00	346
12.00R20	20	J	156/153	8.50	4000	3650	900	900	315	1125	20.50	372
385/65R22.5	20	K	164	11.75	5000		900		389	1072	17.00	

RS606A+



- Aggressive lug tread for powerful grip on or off the road.
- Deep original tread for long life and outstanding traction.
- Special tread compounds help resist cuts, chips, tearing and irregular wear.

Benefits



Off Road



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
385/65R22.5	20	K	164	11.75	5000	900	389 1072	17.00	

RS608AA



- Aggressive lug tread for powerful grip on or off the road.
- Deep original tread for long life and outstanding traction.
- Special tread compounds help resist cuts, chips, tearing and irregular wear.

Benefits



Off Road




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	20	L	148/145	8.25	3150	2900	850	850	279	1056	20.00	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	20.00	318

RS609A+



- Long haul application of trailers.
- For high speed riding on good roads.
- Straight main slots design enhances handling performance and service life.
- with high irregular wear resistance technology.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
425/65R22.5	20	K	165	13.00	5150			825		330	1124	15.00

RS612A



- For regional application of drive axle.
- Applicable to various road surface on freeway.
- With good grip and traction performance.
- Excellent wear resistance and long mileage.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1019	18.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1054	18.50	328
12R22.5	18	L	152/149	9.00	3550	3250	930	930	300	1085	20.00	343
295/80R22.5	18	M	152/149	9.00	3550	3250	900	900	298	1044	21.00	335
315/80R22.5	20	L	156/150	9.00	4000	3350	850	850	312	1076	21.00	351

RS612AA



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
295/80R22.5	22	L	154/149	9.00	3750	3250	850	850	298	1049	19.00	335
315/70R22.5	20	L	154/150	9.00	4000	3350	900	900	314	1018	20.00	351
315/80R22.5	22	L	158/156	9.00	4250	4000	900	900	300	1083	20.00	351

RS617AA



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance;
- Effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road




Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	22	D	152/149	9.00	4250	4000	900	900	300	1087	22.00	343
315/80R22.5	22	D	158/156	9.00	4250	4000	900	900	300	1078	22.00	351

RS618+



- All position.
- Applicable for regional and long haul on caved road.

Benefits



Regional



Long Haul



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Max Load(kg) Dual	Pressure(Kpa) Single	Pressure(Kpa) Dual	Inflated Dimensions SW	Inflated Dimensions ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
315/60R22.5	16	L	152/148	9.75	3550	3150	900	900	313	950	14.80	

RS618A



- Long haul application of trailers.
- For high speed riding on good roads.
- Straight main slots design enhances handling performance and service life.
- with high irregular wear resistance technology.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	L	152/149	9.00	3550	3250	930	930	300	1085	17.50	343
385/65R22.5	20	K	162	12.25	4500		900		386	996	15.00	
425/65R22.5	20	K	165	13.00	5150		825		330	1124	15.00	

RS618AA



- Suitable for all wheel position of middle/long distance buses and steering wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul





Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	20	L	148/145	8.25	3150	2900	850	850	279	1054	16.50	320
12R22.5	22	L	152/149	9.00	4250	4000	900	900	300	1076	16.50	343
295/80R22.5	22	L	154/149	9.00	3750	3250	850	850	298	1044	16.50	335
315/70R22.5	20	L	154/150	9.00	4000	3350	900	900	314	1010	16.50	351
315/80R22.5	22	L	158/156	9.00	4250	4000	900	900	300	1076	16.50	351
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	16.50	318

RS619A



- Strong shoulder lugs provides excellent gripping power on muddy road conditions.
- Tough belt construction for smooth tread wear and longer mileage.
- Special tread compound for high resistance against tread cut.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
6.50R16LT	10	L	107/102	5.50F	975	850	560	560	185	750	12.50	
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	14.00	236
7.50R16LT	14	K	122/118	6.00G	1500	1320	770	770	215	805	14.00	256
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	16.50	278
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1019	17.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1054	18.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	21.50	346
12.00R20	18	J	154/151	8.50	3750	3450	830	830	315	1125	22.00	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1226	22.00	372

RS620A



- Mainly used for rated load and long haul application on steering and trailing axle with good road and high speed.
- The large saturation pattern design offers the best grounding imprint, making the wearance and grounding pressure distribution more uniform.
- A new generation of exterior design makes the tire more attractive.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	L	152/149	9.00	3550	3250	930	930	300	1085	17.50	320
285/60R22.5	18	K	150/147	9.00	3350	3075	900	900	292	926	16.50	

RS621A



- Mainly for drive axle on mining and bad roads with low speed.
- Excellent traction with big block pattern design.
- Special compound supply anti crack and anti puncture performance.
- Good performance on carrying capacity.

Benefits



Off Road




Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	785	20.00	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	819	20.00	255
8.25R16LT	16	L	128/124	6.50H	1800	1600	770	770	235	864	21.00	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	236	986	21.00	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1030	22.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1065	23.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	25.00	346
12.00R20	20	F	156/153	8.50	4000	3650	900	900	315	1125	25.00	372

RS622




- Mainly for drive and trailer axle.
- On-off high way application.
- Excellent traction and brake performance.
- Good carrying capacity and low heating up.

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
325/65R24	22	K	162/160	9.00	4750	4500	850	850	238	1228	19.50	

RS630



- Excellent anti-overloading and excellent wear resistance.
- Wide tread and complex groove angle to improve the irregular wear and long tread life.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
325/95R24	22	K	162/160	9.00	4750	4500	850	850	325	1228	17.00	

RS630+



- For long haul application of truck and all positions wheels on good roads;
- With wide tread design to extend tire service life;
- With excellent water drainage and heat dispersion performance;
- This pattern has performance in low heating up and rolling resistance.

Benefits



Long Haul



Longer Mileage



Wet Performance

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	18	L	149/146	8.25	3250	3000	930	930	279	1054	17.50	320
285/80R22.5	18	M	152/149	9.00	3550	3250	900	900	288	1044	18.00	335
315/80R22.5	20	L	158/150	9.00	4000	3350	850	850	312	1076	18.00	351

RS630A



- TT/TL dual mode.
- Excellent anti-overloading and excellent wear-resistance.
- Wide tread and complex groove angle to improve the irregular wear and long tread life.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
325/95R24	22	K	162/160	9.00	4750	4500	850	850	325	1228	17.00	

RS630A+



- Suitable for all wheel position of middle/long distance buses on good road conditions.
- Reinforced shoulder design can protect the whole tire and improves the safety performance.
- The continuous shoulder pattern can avoid the irregular wear of the tire.
- The pattern design with low rolling resistance gives good comfort and low fuel consumption.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(Kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	18	L	149/146	8.25	3250	3000	930	930	279	1054	21.00	320

RS631A



- For all position wheels.
- Applicable for regional and long haul on paved road.
- With excellent grip and traction, anti-skidding performance low noise;better fuel efficiency.

Benefits



Regional



Long Haul



Longer Mileage

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	164	11.75	5000		900		389	1072	17.00	

RS631AA



- Added more gripping power.
- Tough belt construction for smooth tread wear.
- Special compound for more mileage and cut protection.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	180	K	4500		900		389	1066	16.00	

RS637AA



- Suitable for drive positions.
- Mixed deep tread block, widened tread, increased grip performance.
- Design for on all road of non-paved roads.

Benefits



Regional



Off Road




Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
315/80R22.5	22	K	158/156	9.00	4250	4000	900	900	300	1081	19.00	351

HONGTYRE INTERNATIONAL FZE

Add: NO.43 Bangkok Road, Qingdao Free Trade Zone, Qingdao, China.

Tel: +86-532- 86766013 +86-532- 86768126

+86-532- 86768852 +86-532- 86766033

+86-532- 86768057 +86-532- 86768067

+86-532- 86768860 +86-532- 86768065

Fax: +86-532-86769930

Email: roadshine@hongtyre.com;

Web:www.hongtyre.com;