



ROADSHINE

TRUCK & BUS RADIAL TYRES



CONTENTS

RS601	-----	01
RS601+	-----	02
RS601A	-----	03
RS602	-----	04
RS602A	-----	05
RS603	-----	06
RS604	-----	07
RS604A	-----	08
RS606	-----	09
RS606+	-----	10
RS608	-----	11
RS608+	-----	12
RS609A	-----	13
RS610	-----	14
RS610A	-----	15
RS611	-----	16
RS612	-----	17
RS612+	-----	18
RS612A	-----	19
RS615	-----	20
RS617	-----	21
RS617A	-----	22
RS618	-----	23
RS618A	-----	24
RS618A+	-----	25
RS619	-----	26
RS620	-----	27
RS620+	-----	28
RS620A	-----	29
RS621	-----	30
RS621+	-----	31
RS622	-----	32
RS622A	-----	33
RS629	-----	34
RS630	-----	35
RS630+	-----	36
RS631	-----	37
RS631+	-----	38
RS631A+	-----	39
RS631A++	-----	40
RS634	-----	41
RS635	-----	42
RS637	-----	43

RS601



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	17.00	346

RS601+



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1800	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	16.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	17.00	346
12.00R20	20	K	158/153	8.50	4000	3650	900	900	315	1125	17.50	372

RS601A



- Suitable for steering wheel position of middle/long distance trucks on various road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear groove combine with steel ply provide excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550 3250	930 930	300 1088	17.5	343
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	15.5	351



RS602



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

Benefits



Long Haul




Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.00R16LT	14	L	118/114	5.50F	1320	1180	770	770	200	775	11.50	236
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	14.50	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	15.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	15.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
12.00R20	20	K	156/153	8.50	4000	3650	900	900	315	1125	16.50	372
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	16.50	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	16.50	343
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	16.50	360
11R24.5	16	L	149/146	8.25	3250	3000	830	830	279	1104	16.50	318
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	16.50	318
295/60R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	15.50	335
315/60R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	15.50	351

RS602A



- Suitable for all wheel position of middle/long-distance trucks on various road conditions.
- 3 zigzag grooves combine with lateral sipes on shoulder provides excellent traction and prevents hydroplaning.

Benefits



Long Haul




Longer Mileage



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215 805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600 1400	770 770	215 805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	14.50	278
9.00R20	16	K	144/142	7.00	2800 2850	900 900	259 1018	15.50	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	16.50	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	17.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	18.00	372
12.00R24	20	K	160/157	8.50	4500 4125	900 900	315 1222	17.50	372
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	17.00	351

RS603



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 zigzag longitudinal grooves provides excellent directional driving performance.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	16.50	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	16.50	320

RS604



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.00R16LT	14	L	118/114	5.50F	1320 1180	770 770	200 775	13.00	236
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215 805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600 1400	770 770	215 805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	14.50	278
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	15.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	18.50	346
12.00R20	18	K	154/151	8.50	3750 3450	830 830	315 1125	17.00	372
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	17.00	372
12.00R24	20	K	160/157	8.50	4500 4125	900 900	315 1222	17.00	372
9.5R17.5	16	L	139/137	6.75	2430 2300	850 850	240 842	15.00	270
9.5R17.5	18	J	143/141	6.75	2725 2575	850 850	240 842	15.00	270
215/75R17.5	16	M	127/124	6.00	1750 1600	830 830	211 767	16.00	237
215/75R17.5	18	L	135/133	6.00	2180 2060	830 830	211 767	16.00	237
235/75R17.5	16	L	141/140	6.75	2575 2500	830 830	233 797	16.00	262
235/75R17.5	18	J	143/141	6.75	2725 2575	830 830	233 797	16.00	262
225/80R17.5	16	L	123/122	6.75	1550 1500	750 750	203 803	16.00	255
245/70R19.5	16	M	136/134	7.50	2240 2120	830 830	248 839	16.00	279
265/70R19.5	16	M	140/138	7.50	2500 2360	860 860	262 867	16.00	295
265/70R19.5	18	J	143/141	7.50	2725 2575	860 860	262 867	16.00	295
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	16.50	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	16.50	320
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	18.00	343
13R22.5	18	L	154/151	9.75	3750 3450	830 830	320 1124	18.00	360
295/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	18.00	335
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	18.00	351

RS604A



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Directional mixed pattern design provides extremely good traction and prevent hydroplaning.

Benefits




Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	16.00	255
7.50R16LT	16	L	124/120	6.00G	1600	1400	770	770	215	805	16.00	255
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	23.00	372
245/70R19.5	16	M	136/134	7.50	2240	2120	830	830	248	839	16.00	279
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	23.00	343

RS606



- Driving wheel position for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.
- Strong block design increases braking power and traction performance.

Benefits



Off Road



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
9.00R20	16	K	144/142	7.00	2800 2650	900 900	259 1019	20.50	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	22.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	22.00	346
12.00R20	20	K	159/153	8.50	4000 3650	900 900	315 1125	23.00	372
12.00R24	20	K	160/157	8.50	4500 4125	900 900	315 1222	23.00	372
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	23.00	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	23.00	320
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	23.00	343
285/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	21.00	335
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	21.00	351
11R24.5	16	L	149/146	8.25	3250 3000	830 830	279 1104	23.00	318
11R24.5	18	L	152/149	8.25	3550 3250	930 930	279 1104	23.00	318

RS606+



- Driving wheel position for construction site or on highway purpose.
- Unique sidewall design shows aggressive appearance and protects sidewall of tire from sharp impact.
- Dual tie-bar and wide foot print provide longer lasting tread life. Casing durability.
- Strong block design increases braking power and traction performance.

Benefits



Off Road



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11.00R20	18	J	152/149	8.0	3550	3250	930	930	293	1085	20.5	346
12.00R20	20	J	158/153	8.5	4000	3650	900	900	315	1125	21.5	372



- Suitable for driving position on paved road conditions. Suitable for middle and long haul usage on good road conditions.
- Special groove bottom design strengthens tire block and provides excellent self-cleaning ability.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11R22.5	14	M	144/142	8.25	2800 2650	720 720	279 1050	23.00	320
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	23.00	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	23.00	320
11R24.5	14	L	146/143	8.25	3000 2725	720 720	279 1104	23.00	318
11R24.5	16	L	149/146	8.25	3250 3000	830 830	279 1104	23.00	318
11R24.5	18	L	152/149	8.25	3550 3250	930 930	279 1104	23.00	318
295/75R22.5	14	L	144/141	9.00	2800 2575	760 760	298 1044	23.00	335
295/75R22.5	16	L	146/143	9.00	3000 2725	830 830	298 1044	23.00	335
295/75R22.5	18	L	149/146	9.00	3250 3000	930 930	298 1044	23.00	335
285/75R24.5	14	L	144/141	8.25	2800 2575	760 760	283 1050	23.00	318
285/75R24.5	16	L	147/144	8.25	3075 2800	830 830	283 1050	23.00	318



RS608+



- Suitable for driving position on paved road conditions. Suitable for middle and long haul usage on good road conditions.
- Special groove bottom design strengthens tire block and provides excellent self-cleaning ability.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	L	148/143	8.25	3000	2725	830	830	279	1050	23.00	320
11R22.5	18	M	149/146	8.25	3250	3000	930	930	279	1050	23.00	320
295/75R22.5	16	L	148/143	9.00	3000	2725	830	830	298	1044	23.00	335
295/75R22.5	18	L	149/146	9.00	3250	3000	930	930	298	1044	23.00	335

RS609A



- Suitable for middle/long distance trucks on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
425/65R22.5	20	K	165	13.00	5150	825	430 1124	15.00	

RS610



- Deep and sturdy tread pattern for high mileage, stone & mud clearance. Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	22.00	343

RS610A



- Deep and sturdy tread pattern for high mileage, stone & mud clearance. Stable center blocks minimize tread damage off road service.
- Optimum carcass construction for casing durability and uniform wear.

Benefits



Regional



Longer Mileage



Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215 805	16.50	255
7.50R16LT	16	L	124/120	6.00G	1600 1400	770 770	215 805	16.50	255
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	16.00	278
9.00R20	16	K	144/142	7.00	2800 2850	900 900	259 1018	21.00	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	21.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	23.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	23.00	372
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	23.00	343
285/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	23.00	335

RS611



- Suitable for driving wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 3 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
225/70R19.5	14	L	128/126	6.75	1800	1700	760	760	226	811	17.00	254
225/80R17.5	16	L	123/122	6.75	1550	1500	750	750	203	803	16.00	256
275/70R22.5	16	M	148/145	8.25	3150	2900	900	900	276	958	16.00	311
275/80R22.5	16	M	149/146	8.25	3250	3000	850	850	285	1026	16.00	320
285/75R24.5	14	L	144/141	8.25	2800	2575	760	760	283	1050	21.00	318
285/75R24.5	16	L	147/144	8.25	3075	2800	830	830	283	1050	21.00	318

RS612



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	14.50	278
9.00R20	16	K	144/142	7.00	2800 2850	900 900	259 1018	16.00	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	17.00	328
215/75R17.5	16	M	127/124	6.00	1750 1600	830 830	211 767	16.00	237
215/75R17.5	18	L	135/133	6.00	2180 2060	830 830	211 767	16.00	237
235/75R17.5	16	L	132/129	6.75	2000 1850	830 830	233 797	16.00	262
235/75R17.5	18	J	143/141	6.75	2725 2575	830 830	233 797	16.00	262
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	17.00	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	17.00	320
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	17.00	343
13R22.5	18	L	154/151	9.75	3750 3450	830 830	320 1124	19.50	360
295/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	17.00	335
315/70R22.5	18	M	154/151	9.00	3750 3450	830 830	312 1014	17.00	351
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	17.00	351

RS612+



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	21.00	320
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	21.00	335
315/70R22.5	18	M	154/150	9.00	3750	3350	800	800	312	1014	20.00	351
315/70R22.5	20	M	156/150	9.00	4000	3350	830	830	312	1014	20.00	351
315/80R22.5	18	M	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	23.00	351

RS612A



- Suitable for driving wheel position of middle/long distance trucks on various road conditions.
- Mixed groove pattern with open shoulder provides excellent traction, grip and anti-skid performance.

Benefits



Long Haul



Powerful Traction

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated SW	Dimensions ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550	3250	930	930	300	1083	20.00	343
11R24.5	18	L	152/149	8.25	3550	3250	930	930	279	1104	20.00	318

RS615



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- 4 linear grooves design provides excellent directional driving performance and prevent uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
8.5R17.5	12	L	121/120	6.00	1450	1400	620	620	215	802	13.00	242
9.5R17.5	16	L	139/137	6.75	2430	2300	850	850	240	842	13.00	270
9.5R17.5	18	J	143/141	6.75	2725	2575	850	850	240	842	15.00	270
215/75R17.5	16	M	127/124	6.00	1750	1600	830	830	211	767	14.00	237
215/75R17.5	18	L	135/133	6.00	2180	2060	830	830	211	767	14.00	237
235/75R17.5	16	L	132/129	6.75	2000	1850	830	830	233	797	14.00	262
235/75R17.5	18	J	143/141	6.75	2725	2575	830	830	233	797	14.00	262
265/70R19.5	16	M	140/138	7.50	2500	2360	860	860	262	867	14.00	295
265/70R19.5	18	J	143/141	7.50	2725	2575	860	860	262	867	14.00	295

RS617



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
9.00R20	16	K	144/142	7.00	2800 2650	900 900	259 1018	19.00	306
1000R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	19.00	328
1100R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	19.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	19.00	372
11R22.5	16	M	148/143	8.25	3000 2725	830 830	279 1050	19.00	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	19.00	320
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	19.00	343
13R22.5	18	L	154/151	9.75	3750 3450	830 830	320 1124	23.00	360
285/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	23.00	335
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	23.00	351
11R24.5	16	L	149/146	8.25	3250 3000	830 830	279 1104	23.00	318
11R24.5	18	L	152/149	8.25	3550 3250	930 930	279 1104	23.00	318

RS617A



- Suitable for all wheel positions of earth mover or mine vehicle on hazard road and off road condition.
- Streamline pattern combine with rigid tread chunks provides excellent traction and driving performance.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Off Road



Powerful Traction



Anti-puncture

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550	3250	930	930	300	1093	20.0	343



- Suitable for all wheel position of middle/long distance buses and trailer wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11R22.5	14	M	144/142	8.25	2800 2650	720 720	279 1050	10.50	320
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	10.50	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	10.50	320
11R24.5	14	L	146/143	8.25	3000 2725	720 720	279 1104	10.50	318
11R24.5	16	L	149/146	8.25	3250 3000	830 830	279 1104	10.50	318
11R24.5	18	L	152/149	8.25	3550 3250	930 930	279 1104	10.50	318
295/75R22.5	14	L	144/141	9.00	2800 2575	760 760	298 1044	10.50	335
295/75R22.5	16	L	146/143	9.00	3000 2725	830 830	298 1044	10.50	335
295/75R22.5	18	L	149/146	9.00	3250 3000	930 930	298 1044	10.50	335
285/75R24.5	14	L	144/141	8.25	2800 2575	760 760	283 1050	10.50	318
285/75R24.5	16	L	147/144	8.25	3072 2800	830 830	283 1050	10.50	318

RS618A



- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.00R16LT	14	L	118/114	5.50F	1320 1180	770 770	200 775	14.00	236
7.50R16LT	14	L	122/118	6.00G	1500 1320	770 770	215 805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1600 1400	770 770	215 805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800 1600	770 770	235 855	14.00	278
8.25R20	16	K	138/137	6.50	2430 2300	930 930	232 971	15.50	274
9.00R20	16	K	144/142	7.00	2800 2650	900 900	259 1018	16.50	306
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	15.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	15.00	346
9R22.5	14	L	136/134	6.75	2240 2120	830 830	230 970	15.00	262
10R22.5	16	L	144/142	7.50	2800 2650	900 900	245 1020	16.00	290
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	16.50	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	16.50	320
11R24.5	16	L	149/146	8.25	3250 3000	830 830	279 1104	16.50	318
11R24.5	18	L	152/149	8.25	3550 3250	930 930	279 1104	16.50	318
225/80R19.5	14	L	128/126	6.75	1800 1700	760 760	226 811	13.00	254
225/80R17.5	16	L	123/122	6.75	1550 1500	825 825	203 803	13.00	254
245/70R19.5	16	M	136/134	7.50	2240 2120	830 830	248 839	14.00	279
285/70R19.5	16	M	146/144	8.25	3000 2800	900 900	283 901	14.00	318
255/70R22.5	16	L	140/137	7.50	2500 2300	830 830	255 930	15.00	287
275/70R22.5	16	M	148/145	8.25	3150 2900	900 900	276 958	16.00	311
275/80R22.5	16	M	149/146	8.25	3250 3000	850 850	285 1026	16.00	311
285/75R24.5	14	L	144/141	8.25	2800 2575	760 760	283 1050	16.50	318
285/75R24.5	16	L	147/144	8.25	3075 2800	830 830	283 1050	16.50	318
295/75R22.5	16	L	146/143	9.00	3000 2725	830 830	298 1044	16.50	335
295/75R22.5	18	L	149/146	9.00	3250 3000	930 930	298 1044	16.50	335
315/70R22.5	18	M	154/150	9.00	3750 3350	800 800	312 1014	16.50	351
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	19.00	351



RS618A+



- Suitable for all wheel position of middle/long distance buses and steering and trailer position wheel position of trucks on good road conditions.
- 4 linear tread grooves provides excellent directional driving performance and prevents uneven tire wear.
- Comfortable and safer driving experience, in addition to longer mileage.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11R22.5	18	M	149/146	8.25	3250 3000	830 830	279 1050	15.5	320
12R22.5	18	L	152/149	9.00	3550 3250	930 930	300 1084	15.5	343

RS619



- Suitable for tipper trucks on tough road conditions such as mine and construction site.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom thereby resulting in a safer driving experience.

Benefits



Regional



Longer Mileage




Powerful Traction



Mixed Surface

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	18.50	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	18.50	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	18.50	346

RS620



- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11R22.5	16	M	146/143	8.25	3000 2725	830 830	279 1050	15.00	320
11R22.5	18	M	149/146	8.25	3250 3000	930 930	279 1050	15.00	320
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	15.00	343
295/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	15.00	335
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	15.00	351

RS620+



- Suitable for all wheel positions of middle and long distance coach, steering wheel position of middle and long distance trucks.
- Specially designed for long distance transportation vehicles on good road conditions.
- Comfortable and safer driving experience, In addition to longer mileage.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300		18.00	343
295/80R22.5	18	M	154/151	9.00	3750	3450	830	830	298		18.00	335

RS620A



- Suitable for all wheel positions of middle/long distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear grooves design provides excellent directional driving performance and prevents hydroplaning.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	16.50	343
295/80R22.5	18	M	154/151	9.00	3750 3450	830 830	298 1044	18.00	335

RS621



- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Max Load(kg) Dual	Pressure(Kpa) Single	Pressure(Kpa) Dual	Inflated Dimensions SW	Inflated Dimensions ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
295/60R22.5	16	M	150/147	9.00	3350	3075	830	830	298	1044	23.00	335
295/60R22.5	18	M	154/151	9.00	3750	3450	830	830	298	1044	23.00	335

RS621+



- Suitable for short haul and low-speed trucks on poor road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhance tire mileage for better economy.

Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
11.00R20	18	F	152/149	8.00	3550 3250	930 930	293 1085	23.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	24.00	372

RS622



- Suitable for driving wheel position of vans on various road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Longer Mileage



Powerful Traction



Anti-chipping

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
7.50R16LT	14	L	122/118	6.00G	1500	1320	770	770	215	805	14.00	255
7.50R16LT	16	L	124/120	6.00G	1800	1400	770	770	215	805	14.00	255
8.25R16LT	16	K	128/124	6.50H	1800	1600	770	770	235	855	16.00	278
8.25R20	16	K	139/137	6.50	2430	2300	930	930	232	971	17.50	274
9.00R20	16	K	144/142	7.00	2800	2650	900	900	259	1018	19.00	306
10.00R20	18	K	149/146	7.50	3250	3000	930	930	278	1055	15.00	328
11.00R20	18	K	152/149	8.00	3550	3250	930	930	293	1085	15.00	346
12.00R20	20	K	158/153	8.50	4000	3650	900	900	315	1125	19.00	372
11R22.5	16	M	146/143	8.25	3000	2725	830	830	279	1050	20.00	320
12R22.5	18	K	152/149	9.00	3550	3250	830	830	300	1084	20.00	343
315/80R22.5	18	F	154/151	9.00	3750	3450	830	830	312	1076	21.00	351
315/80R22.5	20	K	157/154	9.00	4125	3750	900	900	312	1076	21.00	351

RS622A



- Suitable for driving wheel position of vans on various road conditions.
- Streamline pattern combine with rigid tread chunks provide excellent traction and driving performance.
- Deeper tread pattern design offers enhanced tire mileage for better economy.
- Reinforced tread block enhances its anti-rupture performance; effectively reducing cracks in groove bottom, thereby resulting in a safer driving experience.

Benefits



Regional



Longer Mileage




Powerful Traction



Anti-chipping

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
10.00R20	18	K	149/146	7.50	3250 3000	930 930	278 1055	21.00	328
11.00R20	18	K	152/149	8.00	3550 3250	930 930	293 1085	21.00	346
12.00R20	20	K	156/153	8.50	4000 3650	900 900	315 1125	21.00	372

RS629



- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.
- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- 4 linear groove design provide excellent directional driving performance and prevent hydroplaning .

Benefits



Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single	Dual	Pressure(Kpa) Single	Dual	Inflated Dimensions SW	ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
13R22.5	18	L	154/151	9.75	3750	3450	830	830	320	1124	15.50	360

RS630



- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12.00R24	20	K	160/157	8.50	4500 4125	900 900	315 1222	16.00	372

RS630+



- Unique groove design prevents stones from getting trapped in the tire grooves.
- Special shoulder design provides excellent protection from uneven tire wear.
- Suitable for all wheel position of middle/long-distance buses and steering wheel position of trucks on good road conditions.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
12.00R24	20	K	160/157	8.50	4500	4125	900	900	315	1222	15.00	372

RS631



- Suitable for middle/long distance on good road conditions.
- 5 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
385/65R22.5	20	K	180	11.75	4500	900	389 1072	16.50	
385/65R22.5	22	K	162	11.75	4750	930	389 1072	16.50	

RS631+



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

Benefits



Long Haul




Powerful Traction



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
385/65R22.5	20	K	160	11.75	4500	900	389 1072	16.50	
385/65R22.5	22	K	162	11.75	4750	930	389 1072	16.50	

RS631A+



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

Benefits



Long Haul



Powerful Traction



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
385/65R22.5	20	K	160	11.75	4500	900	389 1072	16.50	
385/65R22.5	22	K	162	11.75	4750	930	389 1072	16.50	

RS631A++



- New low heat tire shoulder designed to provide excellent high-speed performance.
- Widen tread design effectively increases the wear volume and extend tire life.
- Unique tire shape and strong steel cord structure providing excellent durability performance.

Benefits



Long Haul




Powerful Traction



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
385/65R22.5	20	K	160	11.75	4500		900		389	1072	16.50	
385/65R22.5	22	K	162	11.75	4750		930		389	1072	16.50	

RS634



- Special design for anti-skidding and perfect handling.
- Central tread ensure excellent gripping and reduce rolling resistance.
- Unique technical formula improve the wear-resistance and stability..
- Suitable for middle/long distance on good road conditions.
- 4 zigzag-groove structure provides excellent traction and directional driving performance, as well as cornering stability.

Benefits



Long Haul



Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
285/75R24.5	14	M	144/141	8.25	2800 2575	760 760	283 1050	10.50	318
285/75R24.5	16	M	147/144	8.25	3072 2800	830 830	283 1050	10.50	318

RS635



- Safe and advance pattern design reduce rolling resistance and ensure tire fuel economy and high speed performance.
- Suitable for steering wheel position of middle/long distance trucks on good road conditions.
- Unique tread groove design effectively expels stones from tire groove.
- 5 linear grooves combine with steel ply provide excellent direction driving performance and prevents uneven tire wear.

Benefits



Long Haul




Longer Mileage



Comfort

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg)		Pressure(Kpa)		Inflated Dimensions		Tread Depth (mm)	Min. Dual Spacing(mm)
					Single	Dual	Single	Dual	SW	ODI		
285/75R24.5	14	M	144/141	8.25	2800	2575	760	760	283	1050	16.50	318
285/75R24.5	16	M	147/144	8.25	3072	2800	830	830	283	1050	16.50	318

RS637



- Suitable for drive positions.
- Mixed deep tread block, widened tread, increased grip performance.
- Design for on all types of non-paved roads.

Benefits



Long Haul



Longer Mileage

Vehicle



Size	Ply Rating	Spd	Load Index (single double)	Measure Rim (inch)	Max Load(kg) Single Dual	Pressure(Kpa) Single Dual	Inflated Dimensions SW ODI	Tread Depth (mm)	Min. Dual Spacing(mm)
12R22.5	18	K	152/149	9.00	3550 3250	830 830	300 1084	23.00	342
13R22.5	18	L	154/151	9.75	3750 3450	830 830	320 1124	23.00	360
315/80R22.5	20	K	157/154	9.00	4125 3750	900 900	312 1076	23.00	351

HONGTYRE INTERNATIONAL FZE

Add: NO.43 Bangkok Road, Qingdao Free Trade Zone, Qingdao, China.

Tel: +86-532- 86766013 +86-532- 86768126

+86-532- 86768852 +86-532- 86766033

+86-532- 86768057 +86-532- 86768067

+86-532- 86768860 +86-532- 86768065

Fax: +86-532-86769930

Email: roadshine@hongtyre.com;

Web: www.hongtyre.com;